


Cord Grips

Nickel Plated Brass



Technical Data

Body Material: Nickel Plated Brass
 Gasket Material: Neoprene
 Temperature Range: -68°F to +176°F
 Protection Grade: IP 68



PG Standard Thread Length

Part No.	Thread Size	Cable Ø Range		Dimensions (in)		
		(in)	(mm)	H	TL	W
CG-PG7	PG7	0.118 - 0.256	3 - 6.5	0.748	0.197	0.492
CG-PG7-1		0.079 - 0.197	2 - 5	0.748	0.197	0.492
CG-PG9	PG9	0.157 - 0.315	4 - 8	0.787	0.236	0.598
CG-PG9-1		0.079 - 0.236	2 - 6	0.787	0.236	0.598
CG-PG11	PG11	0.157 - 0.394	5 - 10	0.827	0.236	0.732
CG-PG11-1		0.118 - 0.276	3 - 7	0.827	0.236	0.732
CG-PG13	PG13	0.236 - 0.472	6 - 12	0.866	0.256	0.803
CG-PG13-1		0.197 - 0.354	5 - 9	0.866	0.256	0.803
CG-PG16	PG16	0.394 - 0.551	10 - 14	0.906	0.256	0.886
CG-PG16-1		0.275 - 0.472	7 - 12	0.906	0.256	0.886
CG-PG21	PG21	0.512 - 0.709	13 - 18	0.984	0.276	1.114
CG-PG21-1		0.354 - 0.630	9 - 16	0.984	0.276	1.114
CG-PG29	PG29	0.705 - 0.984	18 - 25	1.142	0.315	1.457
CG-PG29-1		0.512 - 0.787	13 - 20	1.142	0.315	1.457
CG-PG36	PG36	0.866 - 1.260	22 - 32	1.378	0.315	1.850
CG-PG36-1		0.787 - 1.024	20 - 26	1.378	0.315	1.850
CG-PG42	PG42	1.260 - 1.496	32 - 38	1.457	0.354	1.216
CG-PG42-1		0.984 - 1.220	25 - 31	1.457	0.354	1.216
CG-PG48	PG48	1.457 - 1.732	37 - 44	1.496	0.394	2.335
CG-PG48-1		1.142 - 1.378	29 - 35	1.496	0.394	2.335

PG Long Thread Length

Part No.	Thread Size	Cable Ø Range		Dimensions (in)		
		(in)	(mm)	H	TL	W
CG-PG7-L	PG7	0.118 - 0.256	3 - 6.5	0.748	0.394	0.492
CG-PG7-1L		0.079 - 0.197	2 - 5	0.748	0.394	0.492
CG-PG9-L	PG9	0.157 - 0.315	4 - 8	0.787	0.394	0.598
CG-PG9-1L		0.079 - 0.236	2 - 6	0.787	0.394	0.598
CG-PG11-L	PG11	0.157 - 0.394	5 - 10	0.827	0.394	0.732
CG-PG11-1L		0.118 - 0.276	3 - 7	0.827	0.394	0.732
CG-PG13-L	PG13	0.236 - 0.472	6 - 12	0.866	0.394	0.803
CG-PG13-1L		0.197 - 0.354	5 - 9	0.866	0.394	0.803
CG-PG16-L	PG16	0.394 - 0.551	10 - 14	0.906	0.394	0.886
CG-PG16-1L		0.275 - 0.472	7 - 12	0.906	0.394	0.886
CG-PG21-L	PG21	0.512 - 0.709	13 - 18	0.984	0.472	1.114
CG-PG21-1L		0.354 - 0.630	9 - 16	0.984	0.472	1.114
CG-PG29-L	PG29	0.705 - 0.984	18 - 25	1.142	0.472	1.457
CG-PG29-1L		0.512 - 0.787	13 - 20	1.142	0.472	1.457
CG-PG36-L	PG36	0.866 - 1.260	22 - 32	1.378	0.591	1.850
CG-PG36-1L		0.787 - 1.024	20 - 26	1.378	0.591	1.850
CG-PG42-L	PG42	1.260 - 1.496	32 - 38	1.457	0.591	1.216
CG-PG42-1L		0.984 - 1.220	25 - 31	1.457	0.591	1.216
CG-PG48-L	PG48	1.457 - 1.732	37 - 44	1.496	0.591	2.335
CG-PG48-1L		1.142 - 1.378	29 - 35	1.496	0.591	2.335

(+) STANDARD STOCK ITEM

Metric Standard Thread Length

Part No.	Thread Size	Cable Ø Range		Dimensions (in)		
		(in)	(mm)	H	TL	W
CG-M12	M12	0.118 - 0.256	3 - 6.5	0.748	0.197	0.472
CG-M12-1		0.079 - 0.197	2 - 5	0.748	0.197	0.472
CG-M16	M16	0.157 - 0.315	4 - 8	0.787	0.236	0.630
CG-M16-1		0.079 - 0.236	2 - 6	0.787	0.236	0.630
CG-M18	M18	0.197 - 0.394	5 - 10	0.827	0.236	0.709
CG-M18-1		0.118 - 0.276	3 - 7	0.827	0.236	0.709
CG-M20	M20	0.236 - 0.472	6 - 12	0.866	0.256	0.787
CG-M20-1		0.197 - 0.354	5 - 9	0.866	0.256	0.787
CG-M25	M25	0.512 - 0.709	13 - 18	0.984	0.276	0.984
CG-M25-1		0.354 - 0.630	9 - 16	0.984	0.276	0.984
CG-M32	M32	0.709 - 0.984	18 - 25	1.142	0.315	1.260
CG-M32-1		0.512 - 0.787	13 - 20	1.142	0.315	1.260
CG-M40	M40	0.866 - 1.260	22 - 32	1.378	0.315	1.575
CG-M40-1		0.787 - 1.024	20 - 26	1.378	0.315	1.575
CG-M50	M50	1.260 - 1.496	32 - 38	1.457	0.354	1.969
CG-M50-1		0.984 - 1.220	25 - 31	1.457	0.354	1.969
CG-M63	M63	1.457 - 1.732	37 - 44	1.496	0.394	2.480
CG-M63-1		1.142 - 1.378	29 - 35	1.496	0.394	2.480

Metric Long Thread Length

Part No.	Thread Size	Cable Ø Range		Dimensions (in)		
		(in)	(mm)	H	TL	W
CG-M12-L	M12	0.118 - 0.256	3 - 6.5	0.748	0.394	0.472
CG-M12-1L		0.079 - 0.197	2 - 5	0.748	0.394	0.472
CG-M16-L	M16	0.157 - 0.315	4 - 8	0.787	0.394	0.630
CG-M16-1L		0.079 - 0.236	2 - 6	0.787	0.394	0.630
CG-M18-L	M18	0.197 - 0.394	5 - 10	0.827	0.394	0.709
CG-M18-1L		0.118 - 0.276	3 - 7	0.827	0.394	0.709
CG-M20-L	M20	0.236 - 0.472	6 - 12	0.866	0.394	0.787
CG-M20-1L		0.197 - 0.354	5 - 9	0.866	0.394	0.787
CG-M25-L	M25	0.512 - 0.709	13 - 18	0.984	0.472	0.984
CG-M25-1L		0.354 - 0.630	9 - 16	0.984	0.472	0.984
CG-M32-L	M32	0.709 - 0.984	18 - 25	1.142	0.472	1.260
CG-M32-1L		0.512 - 0.787	13 - 20	1.142	0.472	1.260
CG-M40-L	M40	0.866 - 1.260	22 - 32	1.378	0.591	1.575
CG-M40-1L		0.787 - 1.024	20 - 26	1.378	0.591	1.575
CG-M50-L	M50	1.260 - 1.496	32 - 38	1.457	0.591	1.969
CG-M50-1L		0.984 - 1.220	25 - 31	1.457	0.591	1.969
CG-M63-L	M63	1.457 - 1.732	37 - 44	1.496	0.591	2.480
CG-M63-1L		1.142 - 1.378	29 - 35	1.496	0.591	2.480

(+) STANDARD STOCK ITEM