

Part Number: C4119A

Revision Level: 4

Date: 7/16/2007

**4C 20 7/28 TC PVC PVC**

**COMMUNICATION CABLE**

**A. CONSTRUCTION**

Conductor:	#20 AWG 7/28 Tinned Copper	0.038" nom.
Insulation:	0.016" Wall Polyvinyl Chloride	0.070" nom.
Cable:	4 conductors	0.171" nom.
Jacket:	0.032" Wall Polyvinyl Chloride	0.235" +/- 0.012"
Print Legend:	<i>CAROL (R) 20 AWG - C4119A - 105C LL69381 CMG CSA C/US OR AWM I/II A/B 105C 600V FT4 OR AWM STYLE 2464 - - MADE IN USA (DATE CODE &amp; SEQ. FOOTAGE)</i>	

**DIAMETERS**

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 800
Canadian Electrical Code	CSA 22.2 No. 214
UL Subject 758 (CSA)	AWM Style 2464
CSA International	Type CMG Type AWM

**C. ELECTRICAL PROPERTIES**

TEMPERATURE:	105 C
SUGGESTED WORKING VOLTAGE (Vrms):	600 Vrms
CONDUCTOR D.C. RESISTANCE:	10.3 Ohms/1000 ft. nom. @ 20 C

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green