

LED SHOEBOX AREA LIGHTING



X-Power
臺創



Easy installation

Features

Certifications: DLC ETL FCC listed

Power: 60W 100W 150W 200W 300W

Input Voltage: AC100-277V or AC200-480V

Lighting Angle: Type II Type III Type IV Type V

Multi-functions: Photocell Shorting cap Motion sensor Surge protection available

Installations: Arm Mount Slip Fitter Slip Fitter Adapter and Trunnion available





LED SHOEBOX AREA LIGHTING

Basic options



60W 100W



150W 200W



300W

LED Flood Light



60W 100W



150W 200W



300W

Multi-functions



Shorting cap



Photocell




Motion sensor + Photocell


Installation accessories



Arm Mount



Slip Fitter



Trunnion

Specifications for 130lm/W

POWER	60W	100W	150W	200W	300W
Product Size	13"x 12"x 3.6"	13"x 12"x 3.6"	18.2"x 12"x 3.6"	18.2"x 12"x 3.6"	22.9"x 12"x 3.6"
LED Chip	SMD3030	SMD3030	SMD3030	SMD3030	SMD3030
Input Voltage	AC100-277V/AC200-480V	AC100-277V/AC200-480V	AC100-277V/AC200-480V	AC100-277V/AC200-480V	AC100-277V/AC200-480V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
PF	0.9	0.9	0.9	0.9	0.9
Efficiency	130lm/w	130lm/w	130lm/w	130lm/w	130lm/w
LED Luminous Flux	7800lm	13000lm	19500lm	26000lm	39000lm
CCT	4000K /5000K /5700K				
CRI	Ra>80				
LED Node Temperature	<85℃				
Operation Temperature	-40~+45℃				
Storage Temperature	-45~+80℃				
IP Grade	IP65				
LED Lifespan	50,000Hours				
Driver	Build-in				
Lighting Angle	Type II, Type III, Type IV, Type V				
Multi-functions	Photocell, Shorting cap, Motion sensor, Surge protection available				
Installation Available	Arm Mount(For Square or Round Pole), Slip Fitter, Slip Fitter Adapter and Trunnion available				
Certificates	DLC ETL FCC				

Applications

