





The ILUMINAR iLW series LED was specifically created to help with leafy greens, herbs and low clearance indoor horticultural environments. The iLWs sleek low profile engineering allows it to be equipped in low clearance vertical agricultural farms and defoliated area micro green environments making it the ideal LED for most organic farmers to choose. The iLW is available in 40W, 60W and 80W configurations and each LED array in length for each model is 47 inches. The available efficacy in the 40W iLW LED is $2.5~\mu \text{mol/j}$ with the ability to push out up to an outstanding $100+\mu \text{mol/s}$ per unit. With all of these design features and low heat coefficient to the mass of the fixture, the iLW is one of the most versatile LEDs offered in the ILUMINAR LED lineup

SPECIFICATIONS

Light Type Multiple Spectrum LED Diodes

Spectrum Tuned Indoor Full Sun / Customized Spectrum

PPF $100 \,\mu \text{mol/s}$

Efficacy 2.5 μ mol/j

Input Power 40 Watts

Input Voltage | Smart Sensing™ 100V to 277V



40W

ILUMINAR*

PHYSICAL SPECIFICATIONS

47" x 5.1" x 1.5" 2.2 lbs 1199mm x 130 mm x 38mm

SPECIFICATIONS

Mounting height

Emitter Cooling

Waterproof Rating

LED Lifespan (90% of Life)

LED Lighting Solutions

Warranty

>18" to top of Canopy

Passive Thermal Management

IP65

55,000+ hours


5 years



55,000+ Operational Hours



The ILUMINAR LED is designed to outperform the competition and we have added additional diodes and tuned the spectrum to deliver iconic results.



Volts	Amps	Watts
120V	0.35A	40.6W
208V	0.21A	41.2W
240V	0.18A	41.5W
277V	0.16A	41.9W









