

How to apply : One Piece wallcoverings

Step 1.



Remove any dirt or dust using damp soft towel.
Do not use soap or cleaning chemical.

* Once the process is done, please allow your wall to be completely dry before proceeding.

Wallcoverings will not stick well on moisture wall surfaces.

Step 2.



Start at the top of the wallcoverings carefully peel it from backing.

Step 3.



Make a fold and crease ONLY on backing in between 3-5 inches from the top edge, before begins installation.

Step 4.



Once it's in your desired position, start installing from the top side.

Step 5.



Check and make sure there isn't any air bubbles inside as you install.

Step 6.



Gently, push out air bubbles from top to bottom and center to edges. Make sure there isn't any wrinkle on the backside while peeling off. If you weren't able to push out all bubble for the first time you don't need to panic. Gently peel off from the wall and reposition it.



 **Made in Japan**

One Piece Wallcoverings is Official Licensed Products with our exclusive design.
Manufactured by **TOKIWA S.N.C, LTD.**
5-125-1 Yokosone, Ohgaki-city, Gifu,
503-0944 Japan

[Note]

*When applied to the right surface this wallcoverings can be removed without damaging the surface.

[Material]

Made in Japan

Front: Polyester

Adhesive: Acrylic

[Recommended Surfaces]

Smooth and clean walls (completely dry surfaces)

Painted Drywall

Glass*

Metal (Not rusted)

Sanded Wood (Without lacquer)

Inside, temperature controlled environments

[Not Recommended Surfaces]

Freshly painted walls. Wait 30 days after painting before you put up this wallcoverings

Textured walls

Unpainted drywall

Brick

Cinder block

Porous, Textured paneling

Outside, non-temperature controlled environments

*Some cases, wallcovering leaves its stickiness on glass. Please use regular sticker remover or peeler to remove.