

Product Data Sheet

Revised: 2021/11/26 (version 1.1)

PETRONAS Syntium Racer



PETRONAS

10W-60

Developed with °CoolTech™ technology to control engine-damaging heat

With today's smaller, more compact modern engines running hotter than ever, and congested stop/start traffic increasing operating temperatures further, the conditions couldn't be more challenging and hostile for an oil. To achieve maximum thermal efficiency, engines need to stay cool in the face of aggressive heat.

Description and Applications

PETRONAS Syntium Racer 10W-60 is a fully synthetic lubricant developed with °CoolTech™ technology that effectively controls the heat, resisting oxidation and preventing oil degradation and deposit build up, to protect parts and maintain engine efficiency for the full drain interval.

PETRONAS Syntium Racer 10W-60 especially designed for all types of high-powered racing engines, passenger cars including gasoline and diesel engines and latest high-performance cars fitted with fuel injections, multi-valves, turbochargers or superchargers operating under most severe conditions.

Thanks to our experience in Motorsports, powering the most efficient hybrid engine, we developed PETRONAS Syntium, a complete range of lubricants, to help drivers to maximize every drop of energy.

Benefits

PETRONAS Syntium Racer 10W-60 is engineered with °CoolTech™ technology to control the heat, providing enhanced performance and protection through:

- Ultimate power output & performance
- Exceptional protection in all extreme driving conditions.
- Exceptional in keeping engine cleanliness for superior drivability
- Exceptional maintenance of oil pressure at high speeds
- Exceptional start-up under the most extreme conditions for fast response and acceleration
- Exceptional high temperature deposit control to improve drivability and for superior engine performance

Approvals, Specifications and Recommendations

Specifications:

- API SN/CF
- ACEA A3/B4

Performance level:

- FCA 955535-H3 (Performance)

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright and Clear
Density @15°C	ASTM D 4052	g/cm ³	0.862
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	23.1
Viscosity Index	ASTM D 2270	-	180
Flash Point COC	ASTM D 92	°C	>200
Sulphated Ash	ASTM D 874	%	
TBN	ASTM D 2896	mgKOH/g	9.9
CCS at -30°C	ASTM D5293	mPa·s	
Pour Point	ASTM D97	°C	-36

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 70000