



## ARCADIA 9714-0-AAL

<b>COLORWAYS</b>	Bran, Carbon, Chambray, Coffee, Fog, Ink, Nickel, Sandstone, Willow
<b>DESCRIPTION</b>	A lightly textured, yet sturdy fabric with a subtly multicolored weave
<b>END USE</b>	Upholstery
<b>WIDTH</b>	54" wide
<b>REPEAT</b>	No Repeat
<b>WEIGHT</b>	17.088 ounces per yard
<b>CONTENT</b>	100% Polyester
<b>FLAME RESISTANCE</b>	PASSES: NFPA 260, Cal 117-2013
<b>FINISH</b>	Alta™ PFAS Free Performance Technology and Acrylic Backing
<b>ABRASION</b>	ASTM D4157 Wyzenbeek - 120,000 Double Rubs
<b>COLORFASTNESS TO CROCKING</b>	AATCC 8 - Wet: Class 5 / Dry: Class 5
<b>COLORFASTNESS TO LIGHT</b>	AATCC Method 16 (40 hours) - Class 5
<b>PILLING</b>	ASTM D3511 - Class 4.5
<b>SEAM SLIPPAGE</b>	ASTM D4034 -Warp: 31.0 lbs / Fill: 48.5 lbs
<b>BREAKING STRENGTH</b>	ASTM D5034 - Warp: 285 lbs / Fill: 150 lbs

**COUNTRY OF ORIGIN** China  
**NORMAL CARE INSTRUCTIONS**

Spot clean only with a water-free cleaning solvent. Pretest a small, inconspicuous area before proceeding. Do not saturate. DO NOT USE WATER. Pile fabrics may require brushing with a non-metallic, stiff-bristle brush to restore appearance. Cushion covers should not be removed and dry-cleaned. To prevent overall soiling, frequent vacuuming or light brushing with a non-metallic, stiff-bristle brush to remove dust and grime is recommended. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling. Overall cleaning by a professional furniture cleaning service is recommended.

All fabric subject to dye lot variations



\*ACT\* Registered Certification Marks

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.