



CAMILA 9566-0-CAM

COLORWAYS

Base Cloth for print

DESCRIPTION

A plush solid velvet with a low pile and an exceptionally soft hand

END USE

Upholstery

WIDTH

54" Wide

REPEAT

N/A

WEIGHT

17.7 ounces per linear yard

CONTENT

100% Polyester

FLAME RESISTANCE

PASSES: NFPA 260, Cal 117-2013

FINISH

Stain Repellent Finish and Knit Backing

ABRASION

ASTM D4157 Wyzenbeek - 102,000 Double Rubs

COLORFASTNESS TO CROCKING

AATCC 8 - Wet: Class 4.5 / Dry : Class 4.5

COLORFASTNESS TO LIGHT

AATCC Method 16 (40 hours) - Class 4.5

PILLING

ASTM D3511 - Class 5

SEAM SLIPPAGE

ASTM D4034 - Warp: 70 lbs / Fill: 59 lbs

BREAKING STRENGTH

ASTM D5034 - Warp: 134 lbs / Fill: 74.5 lbs

COUNTRY OF ORIGIN

Turkey

NORMAL CARE INSTRUCTIONS

Spot clean only with water-based shampoo or foam upholstery cleaner. Do not use solvents to spot clean. Hot water extraction or steam cleaning is not a recommended cleaning method. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of the affected area to prevent circling.

All fabric subject to dye lot variations

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

