



DUNE 9263-0-DUN

COLORWAYS

Base Cloth for print

DESCRIPTION	Variegated dobby weave with a sturdy, yet natural look and feel
END USE	Upholstery
WIDTH	56" Wide
REPEAT	N/A
WEIGHT	14.88 ounces per linear yard
CONTENT	100% Polyester
FLAME RESISTANCE	PASSES: NFPA 260, Cal 117-2013
FINISH	Alta™ Performance Technology and Acrylic Backing
ABRASION	ASTM D4157 Wyzenbeek - 55,000 Double Rubs
COLORFASTNESS TO CROCKING	AATCC 8 - Wet: Class 5 / Dry: Class 5
COLORFASTNESS TO LIGHT	AATCC Method 16 (40 hours) - Class 3
PILLING	ASTM D3511 - Class 4.5
SEAM SLIPPAGE	ASTM D4034 - Warp: 77.9 lbs / Fill: 77.2 lbs

COUNTRY OF ORIGIN

China

To prevent overall soil, frequent vacuuming or light brushing to remove dust and grime is recommended. Spot clean using a mild water-free solvent or dry cleaning product.

All fabric subject to dye lot variations



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.

LebaTex.com

help@lebatex.com