# LebaTex®
## A STACY GARCIA COMPANY

MADE WITH
## SEAQUAL® YARN

# REEF
# 9730-0-PFAL

| | |
|---|---|
| **COLORWAYS** | Amber, Azure, Driftwood, Fog, Kelp, Lagoon, Ocean, Orchid, Salmon, Sandcastle, Seaglass, Sunshine |
| **DESCRIPTION** | A solid chenille with an incredibly soft hand |
| **END USE** | Upholstery |
| **WIDTH** | 58" wide |
| **REPEAT** | No Repeat |
| **WEIGHT** | 13.79 ounces per linear yard |
| **CONTENT** | 71.28% Polyester, 28.72% Seaqual Polyester |
| **FLAME RESISTANCE** | PASSES: NFPA 260, Cal 117-2013 |
| **FINISH** | Alta™ DWR Performance Technology and Acrylic Backing |
| **ABRASION** | ASTM D4157 Wyzenbeek - 63,000 Double Rubs |
| **COLORFASTNESS TO CROCKING** | AATCC 8 - Wet: Class 4.5 / Dry: Class 4.5 |
| **COLORFASTNESS TO LIGHT** | AATCC Method 16 (40 hours) - Class 4.5 |
| **PILLING** | ASTM D3511 - Class 5 |
| **SEAM SLIPPAGE** | ASTM D4034 - Warp: 92.5 lbs / Fill: 99.5 lbs |
| **BREAKING STRENGTH** | ASTM D5034 Warp: 140 lbs / Fill: 229 lbs |
| **ENVIRONMENTAL** | PFAS Free |
| **COUNTRY OF ORIGIN** | USA |
| **NORMAL CARE INSTRUCTIONS** | |

Spot clean with upholstery shampoo, foam from a mild detergent, or mild cleaning solvent. Pretest a small, inconspicuous area before proceeding. Do not saturate. Pile fabrics may require brushing with a non-metallic, stiff-bristle brush to restore appearance. Hot water extraction or steam cleaning is not a recommended cleaning method. Cushion casings should not be removed and laundered or dry-cleaned. To prevent overall soiling, frequent vacuuming or light brushing with a non-metallic stiff-bristle brush to remove dust and grime is recommended. When cleaning a spill, blot immediately to remove spilled material. Clean spots or stains from the outside to the middle of affected area to prevent circling. Use a professional furniture cleaning service when an overall soiled condition has been reached.

All fabric subject to dye lot variations

*ACT® Registered Certification Marks

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.