



SANIBEL 9119-0-SDW

COLORWAYS Brindle, Cliff, Dove, Ecru, Indigo, Pebble, Shale

DESCRIPTION Solid-color weave with lightly three-dimensional texture

END USE Indoor/Outdoor Upholstery

WIDTH 54" wide REPEAT No Repeat

WEIGHT 20.41 ounces per linear yard

CONTENT

100% Bella-Dura® Solution Dyed Polyolefin

FLAME RESISTANCE

PASSES: NFPA 260/UFAC, Cal 117-2013

FINISH

Wash and Frame; Inherently Stain Resistant

ABRASION

ASTM D4157 Wyzenbeek - 100,000 Double Rubs

COLORFASTNESS TO CROCKING AATCC 8 - Wet: Class 4.5 / Dry: Class 4.5

COLORFASTNESS TO LIGHT AATCC 16 - Meets or exceeds 1500 lightfast hours

PILLING ASTM D3511 - Class 4.5

SEAM SLIPPAGE ASTM D4034 - Warp: 65 lbs / Fill: 106 lbs
BREAKING STRENGTH ASTM D5034 - Warp: 324 lbs / Fill: 476 lbs

SUSTAINABILITY PFAS Free, Recyclable

COUNTRY OF ORIGIN NORMAL CARE INSTRUCTIONS

USA

For Light Stains: A mild soap and water solution is all that is required for most spills. (Detergents are effective cleaners, but their harshness may affect the water-repellent characteristics.) 1. Apply a cleaning solution of 1 part soap to 10 parts water to the fabric. 2. Rinse with clear water to remove any soapy residue. 3. Blot with a clean, dry cloth and allow time to air dry. 4. Repeat as necessary until the stain is gone.

For Stubborn Stains (Bleach Cleanable) Some stubborn stains may require light agitation with an upholstery cleaning brush or toothbrush. Never use stiff bristles or wire brushes, as they may damage the fabric. To prevent overall soil build-up, frequent vacuuming is recommended. 1. Apply a cleaning solution of 1 part bleach to 4 parts water to the fabric. 2. Rinse with clear water to remove any bleach solution residue. 3. Blot with a clean, dry cloth and allow time to air dry. 4. Repeat as necessary until the stain is gone.

All fabric subject to dye lot variations



LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.