



SOLSTICE 9031-0-SDW

COLORWAYS

Bayou, Chambray, Cliff, Cyan, Ink, Moon, Pacific, Persimmon, Shale, Umber

DESCRIPTION

Cross-hatched colors interwoven

END USE

Indoor/Outdoor Upholstery

WIDTH

54" wide

REPEAT

No Repeat

WEIGHT

13.03 ounces per linear yard

CONTENT

100% Bella-Dura® Solution Dyed Polyolefin

FLAME RESISTANCE

PASSES: NFPA 260/UFAC, Cal 117-2013

FINISH

Wash and Frame; Inherently Stain Resistant

ABRASION

ASTM D4157 Wyzenbeek - 100,000 Double Rubs

COLORFASTNESS TO CROCKING

AATCC 8 - Wet: Class 5 / Dry: Class 5

COLORFASTNESS TO LIGHT

AATCC 16 - Meets or exceeds 1500 lightfast hours

PILLING

ASTM D3511 - Class 4.5

SEAM SLIPPAGE

ASTM D4034 - Warp: 38.5 lbs / Fill: 83 lbs

BREAKING STRENGTH

ASTM D5034 - Warp: 357 lbs / Fill: 326 lbs

SUSTAINABILITY

PFAS Free, Recyclable

COUNTRY OF ORIGIN

USA

NORMAL CARE INSTRUCTIONS

For Light Stains: A mild soap and water solution is all that is required for most spills. (Detergents are effective cleaners, but their harshness may affect the water-repellent characteristics.) 1. Apply a cleaning solution of 1 part soap to 10 parts water to the fabric. 2. Rinse with clear water to remove any soapy residue. 3. Blot with a clean, dry cloth and allow time to air dry. 4. Repeat as necessary until the stain is gone.

For Stubborn Stains (Bleach Cleanable) Some stubborn stains may require light agitation with an upholstery cleaning brush or toothbrush. Never use stiff bristles or wire brushes, as they may damage the fabric. To prevent overall soil build-up, frequent vacuuming is recommended. 1. Apply a cleaning solution of 1 part bleach to 4 parts water to the fabric. 2. Rinse with clear water to remove any bleach solution residue. 3. Blot with a clean, dry cloth and allow time to air dry. 4. Repeat as necessary until the stain is gone.

All fabric subject to dye lot variations

LebaTex recommends the end use of a product as specified on the spec sheet only. It is the customer's responsibility to determine code compliance if a product is to be used in a way other than its recommended end use. If a product is ultimately selected and installed in an application that it was not intended for, all liability falls to the customer.



ACT Registered Certification Marks