

# Lipstick Serial Device Server Specification

## USR-DR132/134



## Introduction

The USR-DR13X, launched by PUSR, is an ultra-compact DIN rail-mounted industrial-grade serial port server. It enables fast bidirectional data transmission between RS232/RS485 serial ports and RJ45 Ethernet ports, featuring an integrated TCP/IP protocol stack and expanded Modbus gateway capabilities. This allows seamless integration of devices into industry scenarios, facilitating rapid business framework deployment and saving human resource investments.

This product series adheres to industrial design standards, supporting wide voltage terminal power supply. RS232/RS485 communication modes support baud rates ranging from 600 to 230400bps, withstanding high and low temperatures and ensuring stable operation 24/7, unaffected by harsh environmental conditions. Having undergone rigorous market testing over the years, this series has gained recognition and extensive application in various industries such as finance, transportation, large-scale corporate networks, and factory manufacturing projects.

## Product Features

- Supports both RS232 and RS485 serial signals, allowing for the selection of different specifications as needed, saving project costs.
- Flexible operating modes including TCP Client, TCP Server, UDP Client, UDP Server, and HTTPD Client.
- Enables Modbus gateway functionality for seamless integration between ModbusRTU and Modbus TCP protocols.
- Automatic polling of Modbus commands for millisecond-level data acquisition, with optional transparent or JSON protocol data reporting to servers.
- TCP Server supports up to 16 client connections, displaying connected IPs and calculating data transmission/reception based on connections.
- In TCP Server mode, when the maximum connection limit is reached, the option to kick out old connections for new ones is available.
- Features timeout restart (restart without data) with configurable time settings.
- Custom registration and heartbeat packet mechanisms ensure genuine and reliable connections, eliminating dead connections.
- DHCP functionality for automatic IP acquisition; configurable DNS server address for domain name resolution.
- 10/100Mbps adaptive Ethernet interface supports AUTO-MDIX for automatic switching between crossover and straight-through cables.
- Supports virtual serial ports, compatible with independently developed USR-VCOM software.
- Unique MAC address burned in during factory production, with support for both software and hardware factory reset.
- Industrial-grade design with hardware watchdog for ultra-high reliability.

## Dimensions

Unit: mm



Figure 1 Dimension of USR-DR132/134

## Specifications

Catalog	Parameters	Value
Power Supply	Power Input	5-24V DC
	Working Current	<b>97mA@5V</b>
	Power Interface	Push-type Connector
Hardware Interface	Ethernet Port	1*RJ45, 10/100Mbps, auto MDI/MDIX
	Serial Pors	USR-DR132: 1*RS232 USR-DR134: 1*RS485
	Baud Rate	600~230.4K
	Data bits	7, 8
	Stop bit	1, 2
	Parity bit	Odd, Even, Mark, Space supported when data bits are 7; None, Odd, Even supported when data bits are 7
	Reload Button	Reset to factory settings
	Indicators	POW, WORK, COM, LINK
Physical Parameters	EMC Protection	IEC 61000-4-2 (ESD): Level 2 IEC 61000-4-4 (EFT): Level 2 IEC 61000-4-5 (Surge): Level 2
	Dimension	74*24*22 mm
	Installation	35mm DIN-Rail, Mounting Hole
	Operating Temperature	-40~85°C
	Storage Temperature	-40~105°C
	Operating Humidity	5%~95% RH (non-condensing)
	Storage Humidity	5%~95% RH (non-condensing)
Software	Network Protocols	TCP/UDP/HTTP/IPV4/ICMP/DHCP/ARP
	IP Address	DHCP, Static
	DNS	Configurable DNS
	Configuration	AT Command, Built-in webpage, Config Utility
	Work Mode	TCP Client, TCP Server, UDP Client, UDP Server, HTTP Client
	Modbus Gateway	Modbus RTU/TCP protocol conversion, Modbus Polling, Modbus RTU to Json
	TCP Server	Up to 16 clients
	Packaging mechanism	Packaging Time: 4-byte data transmission time Packaging Length: 400 Bytes

## Purchase & Support

### ■ For more information, please visit our websites:

- Official website: <https://pusr.com>
- Official shop: <https://shop.usriot.com>
- Technical support: <http://h.usriot.com/>



**Your Trustworthy Smart IOT Partner**



Official Website: [www.pusr.com](http://www.pusr.com)

Official Shop: [shop.usriot.com](http://shop.usriot.com)

Technical Support: [h.usriot.com](http://h.usriot.com)

Inquiry Email: [inquiry@usriot.com](mailto:inquiry@usriot.com)

Skype & WhatsApp: +86 13405313834

Click to view more: [Product Catalog](#) & [Facebook](#) & [Youtube](#)