



401 South Grand Ave., Santa Ana, CA 92705  
Tel: 714.550.6070 Fax: 714.550.9661 www.twobros.com



## 2002-03 Honda RC51

V.A.L.E.™ High Mount Slip-on Exhaust System with M-2 Canister  
Part # 005-950406HM, 005-950407HM, 005-950408HM, 005-950419HM, 005-950420HM



### Parts List

Qty.	Description	Part Number
1	Muffler Left	Varies
1	Muffler Right	Varies
1	S-Bend Tube Set	005-9504NHR
2	Muffler Clamps	Varies
1	HARDWARE KIT	005-95H-3
2	VALE Adapter Kit	005-2-1-V
4	80mm swivel hook spring	005-S80
2	Barrel Clamp	005-27-61MSH
6	8x20mm Socket Head Cap Screws	005-SH820
8	8mm Flat Washers	005-WF8
2	8mm Nylon Lock Nuts	005-NN8
1	High Mount AL Brackets (set)	005-9504HB
1	Flush Mount Turn Signals (set)	005-88T
4	Blue Scotch Locks	005-BS
1	Permatex Ultra Black Gasket Maker	031-P22072
1	T20 Torx Screw Wrench	005-9-15820
1	TBR Sticker Kit	015-10212

### IMPORTANT - PLEASE READ CAREFULLY

**We recommend that this performance part be installed by a qualified motorcycle technician. If you have any doubts as to your ability to install this performance part, please consult with your local motorcycle dealer. Read all instructions first before starting installation. Make sure the motorcycle and exhaust system are completely cool before starting the installation. Also, make sure the bike is secure on a center stand or ideally a service lift during installation. Be sure to save all stock components for possible use later.**

### Installation Instructions

1. Make sure the bike is completely cool before starting the installation. Make sure the bike is secure on the sidestand or ideally a rear service stand.
2. Loosen the clamps that holds the connector pipes to the headers under the bike.
3. Remove the bolts that attach the connector pipes to the footpegs.
4. Remove the hardware that holds the stock canisters at the passenger footpeg brackets. Take off the canisters.
5. Remove the seat and rear cowl (refer to Honda owner's manual). Remove the passenger footpegs and replace with high mount hanger brackets. Use the 8mm bolts and washers to secure.
6. Remove the stock rear turn signals and replace with the provided flush mount turn signals. Use the scotch locks to splice into the stock wiring harness.
7. Slide the S-bends onto the end of the headers (you will NOT be using the gaskets), using the T-bolt clamp to attach them to the headers. Our s-bends DO NOT attach to the bottom of the rearsets. Leave loose for now.
8. Install VALE adapter kit using the supplied kit instructions.
9. Place a bead of the hi-temp sealant on the outside edge of the s-bend that goes into the canisters. Slide the TBR canisters onto the end of the S-bend pipes. Wipe off the excess sealant that will squeeze out.
10. Carefully slide the canister clamps over the canisters. (Note: The stainless steel canister clamp and the name badge on the canister come from the factory with a clear plastic protective film. Please remove this film before operation.) You may need to twist and turn the S-bends a little to get it in the right place. Locate both tabs of the canister clamps on the INSIDE of the high mount brackets. Use the 8mm bolts, 8mm nuts and 8mm washers to secure it. Leave loose for now.
11. Make sure everything is aligned and tighten all hardware. Affix the connector springs to the muffler. Reinstall the rear cowl and seat.
12. Before you run the bike, clean off all fingerprints and dirt, as any oily residue will etch the metal and become somewhat permanent when the system gets hot. Run the bike and enjoy. It is normal for some white smoke to appear the first time you start the bike. This is packing/manufacturing oil from inside the pipe burning off. Check for gaps or leaks. If you find a leak, a little high temperature silicon sealant should fix it. After 50 to 100 miles, recheck all fasteners for tightness.

### Care & Cleaning

#### Care & Cleaning

Keep system free of dirt and moisture. Store in a cool, dry place. For cleaning use a mild spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

**Stainless Header System:** Polished stainless steel pipes will turn a light golden hue after a few heat cycles, this is a normal characteristic of high quality stainless steel.

**Carbon Fiber Mufflers:** Always make sure the fiberglass packing inside is in good condition and not burned out, as exhaust heat inside an empty canister will deteriorate the Carbon Fiber sleeve. TBR sells repack kits (TBR part # 005-10038) that include new rivets and repack material as well as a drill bit (#30), making it easy to do yourself. Also, NEVER dyno test your bike with carbon fiber mufflers installed - the intense heat and lack of cooling air can quickly cause the CF material to burn. Two Brothers Racing does not provide a warranty for burned carbon fiber.

**Aluminum Mufflers:** Use an aluminum or mag wheel polish such as Mother's to restore the bright finish to factory spec.

Repack all road canisters every 3,000 miles. Part #005-10038

### Warranty

Two Brothers Racing products are intended for closed course competition purposes only, and therefore are sold "as is" without warranty. Two Brothers Racing specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products or parts.