



401 South Grand Ave., Santa Ana, CA 92705
Tel: 714.550.6070 Fax: 714.550.9661 www.twobros.com



2009 Kawasaki ZX-6R

V.A.L.E.™ Slip-on Exhaust System with M-2 Canister
Part # 005-2410406V, 005-2410407V, 005-2410408V



Parts List

Qty.	Description	Part Number
1	Muffler Canister	Varies
1	Muffler Clamp	Varies
1	Slip-on Tube	005-24104S
1	HARDWARE KIT	005-241-3
2	X-Ring (half)	005-7-2-3
1	Fender Bracket	005-19904B
2	Lighted License Plate Bolt	005-8504LTZ
1	Turn Signals (set of 2)	005-88T2
6	Butt Splice Connectors	005-BS1614
1	Zip Tie	005-ZT458B
1	Zip Tie Tab	005-ZTM4
1	Muffler Bracket	005-241-B
1	8x40mm Socket Head Cap Screw	005-SH840
4	6x14mm Socket Head Cap Screw	005-SH614
4	6mm Split Lock Washer	005-WL6
4	6mm Flange Nut	005-FN6
1	8x16mm Flange Bolt	005-FB816
2	8mm Flange Nut	005-FN8
1	T20 Torx Screw Hex Key	005-9-15820
1	5mm Long Handle Ball End Hex Wrench	005-9-18610
1	TBR Sticker Kit	015-10212

IMPORTANT - PLEASE READ CAREFULLY

We recommend that this performance part be installed by a qualified motorcycle technician. If you have any doubts as to your ability to install this performance part, please consult with your local motorcycle dealer. Read all instructions first before starting installation. Make sure the motorcycle and exhaust system are completely cool before starting the installation. Also, make sure the bike is secure on a centerstand or ideally a service lift during installation. Be sure to save all stock components for possible use later.

Installation Instructions

1. Make sure the bike is completely cool before starting the installation. Make sure the bike is secure on a centerstand or ideally a service lift.

2. Remove side covers and seat.



3. Remove rear passenger seat.

4. Remove OEM rear fender. You will reuse the fender bolts.



5. Remove rear exhaust cover.



6. Remove exhaust valve cables from servo under seat. Use a wrench to hold server wheel in place or internal gears may break.



*Keep servo plugged into harness but cables will not be used.

7. Remove OEM muffler assembly.



8. Attach TBR muffler to slip-on tube using 2 piece X-Ring and the 4 6x14mm S.H.C.S. and lock washers provided. Leave loose for now.



9. Remove lower rear set mounting bolt and replace with supplied 8x40mm socket head cap screw.



10. Attach the supplied mounting bracket to the inside of frame and secure in place with the supplied 8mm flange nut. Bracket should be installed as shown in picture.



11. Install rubber lined muffler clamp over canister.



Continued on pg. 2




401 South Grand Ave., Santa Ana, CA 92705
Tel: 714.550.6070 Fax: 714.550.9661 www.twobros.com



2009 Kawasaki ZX-6R

V.A.L.E.™ Slip-on Exhaust System with M-2 Canister
Part # 005-2410406V, 005-2410407V, 005-2410408V

WIRING DIAGRAM



Warranty

Two Brothers Racing products are intended for closed course competition purposes only, and therefore are sold "as is" without warranty. Two Brothers Racing specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products or parts.

Installation Instructions

12. Install the TBR muffler assembly and attach using the flange bolt and nut to secure the muffler in place.



13. Check alignment and tighten muffler and the 4 6x14mm V.A.L.E.™ socket head cap screws.



14. Tighten OEM joint clamp.
15. Install TBR fender eliminator kit using the original bolts and supplied nuts, the nuts will be inside the bike under seat.
16. Attach turn signals and plate light bolts using the wire splice connectors supplied to the correct wires in the harness as shown in the Wiring Diagram.
17. Re-install seats and covers.
18. Double check all your work.
19. Before you run the bike, clean off all fingerprints and dirt, as any oily residue will etch the metal and become somewhat permanent when the system gets hot. Also, remove any plastic film from the name badge(s) and/or canister clamp(s). Run the bike and enjoy. It is normal for some white smoke to appear the first time you start the bike. This is packing/manufacturing oil from inside the pipe burning off. Check for gaps or leaks. If you find a leak, a little high temperature silicon sealant should fix it. After 50 to 100 miles, recheck all fasteners for tightness.





401 South Grand Ave., Santa Ana, CA 92705
Tel: 714.550.6070 Fax: 714.550.9661 www.twobros.com



2009 Kawasaki ZX-6R

V.A.L.E.™ Slip-on Exhaust System with M-2 Canister
Part # 005-2410406V, 005-2410407V, 005-2410408V



005-2410406V

005-2410407V

005-2410408V



Qty.	Description	Part Number
1	Muffler Canister	005-147-206
1	Muffler Clamp	005-2C
1	Slip-on Tube	005-24104S
1	HARDWARE KIT	005-241-3
2	X-Ring (half)	005-7-2-3
1	Fender Bracket	005-19904B
2	Lighted License Plate Bolt	005-8504LTZ
1	Turn Signals (set of 2)	005-88T2
6	Butt Splice Connectors	005-BS1614
1	Zip Tie	005-ZT458B
1	Zip Tie Tab	005-ZTM4
1	Muffler Bracket	005-241-B
1	8x40mm Socket Head Cap Screw	005-SH840
4	6x14mm Socket Head Cap Screw	005-SH614
4	6mm Split Lock Washer	005-WL6
4	6mm Flange Nut	005-FN6
1	8x16mm Flange Bolt	005-FB816
2	8mm Flange Nut	005-FN8
1	T20 Torx Screw Hex Key	005-9-15820
1	5mm Long Handle Ball End Hex Wrench	005-9-18610
1	TBR Sticker Kit	015-10212

Qty.	Description	Part Number
1	Muffler Canister	005-147-207
1	Muffler Clamp	005-2C1
1	Slip-on Tube	005-24104S
1	HARDWARE KIT	005-241-3
2	X-Ring (half)	005-7-2-3
1	Fender Bracket	005-19904B
2	Lighted License Plate Bolt	005-8504LTZ
1	Turn Signals (set of 2)	005-88T2
6	Butt Splice Connectors	005-BS1614
1	Zip Tie	005-ZT458B
1	Zip Tie Tab	005-ZTM4
1	Muffler Bracket	005-241-B
1	8x40mm Socket Head Cap Screw	005-SH840
4	6x14mm Socket Head Cap Screw	005-SH614
4	6mm Split Lock Washer	005-WL6
4	6mm Flange Nut	005-FN6
1	8x16mm Flange Bolt	005-FB816
2	8mm Flange Nut	005-FN8
1	T20 Torx Screw Hex Key	005-9-15820
1	5mm Long Handle Ball End Hex Wrench	005-9-18610
1	TBR Sticker Kit	015-10212

Qty.	Description	Part Number
1	Muffler Canister	005-147-208
1	Muffler Clamp	005-2C2
1	Slip-on Tube	005-24104S
1	HARDWARE KIT	005-241-3
2	X-Ring (half)	005-7-2-3
1	Fender Bracket	005-19904B
2	Lighted License Plate Bolt	005-8504LTZ
1	Turn Signals (set of 2)	005-88T2
6	Butt Splice Connectors	005-BS1614
1	Zip Tie	005-ZT458B
1	Zip Tie Tab	005-ZTM4
1	Muffler Bracket	005-241-B
1	8x40mm Socket Head Cap Screw	005-SH840
4	6x14mm Socket Head Cap Screw	005-SH614
4	6mm Split Lock Washer	005-WL6
4	6mm Flange Nut	005-FN6
1	8x16mm Flange Bolt	005-FB816
2	8mm Flange Nut	005-FN8
1	T20 Torx Screw Hex Key	005-9-15820
1	5mm Long Handle Ball End Hex Wrench	005-9-18610
1	TBR Sticker Kit	015-10212

Care & Cleaning

Care & Cleaning

Keep system free of dirt and moisture. Store in a cool, dry place. Make sure vehicle is completely cool before maintenance.

Stainless Header System: Polished stainless steel pipes will turn a light golden hue after a few heat cycles, this is a normal characteristic of high quality stainless steel. Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

Titanium Header System: Polished titanium pipes will experience color shift ranging from deep blue/purple through amber after a few heat cycles. This is a normal characteristic of high quality titanium. Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

Polished Aluminum Canisters: Use an aluminum or mag wheel polish to restore the bright finish to factory spec.

Brushed Aluminum Canisters: Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

Carbon Fiber Canisters: Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth. Always make sure the fiberglass packing inside is in good condition and not burned out, as exhaust heat inside an empty canister will deteriorate the carbon fiber sleeve. TBR sells repack kits (Road - #005-10038, Offroad - #005-10038MX) that include everything you need to easily do it yourself.

Titanium Mufflers: For cleaning use a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth. Always make sure the fiberglass packing inside is in good condition and not burned out, as exhaust heat inside an empty canister will deteriorate the carbon fiber sleeve. TBR sells repack kits (Road - #005-10038, Offroad - #005-10038MX) that include everything you need to easily do it yourself.

Repack all road canisters at the first signs of packing material deterioration, Part #005-10038
Repack all offroad canisters after every 10 hours of use. Part #005-10038MX

NEVER dyno test your bike with carbon fiber or titanium canisters installed - the intense heat and lack of cooling air can quickly burn through the canister material. Two Brothers Racing does not provide a warranty for burned canisters.