



401 South Grand Ave., Santa Ana, CA 92705  
Tel: 714.550.6070 Fax: 714.550.9661 www.twobros.com

Harley Davidson  
**FL Touring**  
Part # 034-387-01-V

**COMP V**



Qty.	Description	Part Number
1	Comp-V Assembly	034-387-01-V
1	V-Stack	017C-103
1	Gasket	017C-122
2	Banjo Bolt	017C-117
2	Spacers	017C-104
6	O-Ring	017C-111
1	Thread Locker	031-P09178
1	Anti-Seize	031-P09175
1	Zip-Tie	005-ZT458B




**Installation Instructions**


1. Remove OEM air filter assembly.



2. Remove plug from back of OEM backing plate and zip-tie out of way.



3. Disassemble Comp-V to backing plate.



4. Install one o-ring onto each banjo bolt.



5. Install one o-ring onto each end of the oil-channel spacer.




6. Install gasket onto back of backing plate (this may need to be flipped and turned to find the right bolt pattern).



7. Put banjo bolts through backing plate and spacers. Apply loc-tite to banjo bolt threads.



8. When installing backing plate to throttle body be sure to tighten socket head screws and banjo bolts evenly 1/4 turn at a time to ensure no binding. (Socket head screws are self locking and some slight resistance is normal when tightening.)





401 South Grand Ave., Santa Ana, CA 92705  
 Tel: 714.550.6070 Fax: 714.550.9661 www.twobros.com

# COMP V

**Harley Davidson**  
**FL Touring**  
 Part # 034-387-01-V



Qty.	Description	Part Number
1	Comp-V Assembly	034-387-01-V
1	V-Stack	017C-103
1	Gasket	017C-122
2	Banjo Bolt	017C-117
2	Spacers	017C-104
6	O-Ring	017C-111
1	Thread Locker	031-P09178
1	Anti-Seize	031-P09175
1	Zip-Tie	005-ZT458B

### Installation Instructions

- Install TBR air filter and face plate. Tighten the five socket head cap screws.



- Apply anti-seize to threads of plug cap or v-stack and install hand tight.



### Care & Cleaning

#### Care & Cleaning

Keep system free of dirt and moisture. Store in a cool, dry place. Make sure vehicle is completely cool before maintenance.

### Warranty Information

Two Brothers Racing products are intended for closed course competition purposes only, and therefore are sold "as is" without warranty. Two Brothers Racing specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products or parts. Not tested for use with OEM or aftermarket accessories.

### IMPORTANT - PLEASE READ CAREFULLY

*Two Brothers Racing products are intended for closed course competition purposes only.*

*We recommend that this performance part be installed by a qualified motorcycle technician. If you have any doubts as to your ability to install this performance part, please consult with your local motorcycle dealer. Read all instructions first before starting installation. Make sure the motorcycle and exhaust system are completely cool before starting the installation. Also, make sure the bike is secure on a center stand or ideally a service lift during installation. Be sure to save all stock components for possible use later.*

