

Mfg: Takegawa Make: Honda XR50R

Year: All

Product: Breather Pipe (for use with stock head)



Parts List

- 1- Vented Tappet Cover with O-ring
- 1- Clamp
- 1- Clear Hose (100cm length)
- 6- Zip Ties

Care & Cleaning / Warranty

Warranty

Two Brothers Racing products are intended for closed course competition purposes only, and therefore are sold "as is" without warranty. Two Brothers Racing specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products or parts.

IMPORTANT - PLEASE READ CAREFULLY

We recommend that this performance accessory be installed by a qualified motorcycle technician. If you have any doubts as to your ability to install this accessory, please consult with your local motorcycle dealer. Read all instructions first before starting installation. Make sure the motorcycle and exhaust system are completely cool before starting the installation. Also, make sure the bike is secure on the sidestand or ideally a rear service stand during installation. Be sure to save all stock components for possible use later.

Installation Instructions

- Make sure the bike is completely cool before starting the installation.
- 2. Remove seat and fuel tank.
- 3. Remove intake tappet cover, use a 17mm wrench.
- 4. Install the new vented tappet cover, gently tighten.
- Install clear hose with supplied clamp onto vented tappet cover.

- Route house as shown and secure with supplied zip ties. Do not crush hose with zip ties.
- 7. Hose should be flush with end of subframe. Cut excess length from hose.
- 8. Reinstall seat and fuel tank.

NOTE- Be sure to plug hose when washing bike. Do not get water down the hose!



Takegawa Breather Pipe Instructions.qxd