

Product Spec Sheet

Mohawk moistureGuard™

The standard in sound and moisture protection

Protects floor with quality moisture protection while offering basic sound properties.

- Pre-attached moisture barrier helps protect floor from moisture damage
- Self-leveling
- Recyclable
- Easy to install with attached lip and tape
- Safe for under floor heating
- Odorless
- Mold resistant
- Warranty is the same as your Mohawk floor

Product Information

Name	moistureGuard™
Style Number	LU8A
Material Number	QSCOMBIFLOR100
Universal Product Code	6-36738-41560-3
Dimensions - Standard	40" W x 30' L x .118" Thickness
Dimensions - Metric	1.02 m x 9.14 m x 3 mm
Weight Per Roll	1.98 lbs.
Lip & Tape	Yes
Lip Size - inches	3
Sq Ft per roll	100
Rolls per Box	30
Pallets Per Truck	78
Rolls Per Full Truckload	2340

Product Specifications

Material	Polyethylene Foam
Foam Color	Green Foam
Film Color	Clear - 30% recycled content
Sound Transmission Class (STC)	67
Impact Insulation Class (IIC)	68
Foam Density (lbs/ft ³)	1.2
Thickness	3 mm
Moisture Barrier	2 mil
Chemical Resistance	Very Good
Water Absorption (lbs./sq.ft ²)	0.09
Water Vapor Transmission Rating	0.06
R Value	1.4
Compression Strength (psi)	3.33
Mold and Mildew Resistant	YES