

TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1500 | roll to glue

Permanently elastic polyurethane flooring according to EN 16776
free of chlorine, solvents and plasticizers



	chip ∞	wood ∞	fusion ∞	
Format	20 x 2 m	20 x 2 m	20 x 2 m	
Product thickness	2.5 mm	2.5 mm	2.5 mm	
Weight	3.6 kg/m ²	3.6 kg/m²	3.6 kg/m ²	
Roll / m²	1 / 40 m ²	1 / 40 m²	1 / 40 m ²	
Rolls / m² per pallet	6 / 240 m ²	6 / 240 m²	6 / 240 m ²	
Guarantee	10 years – Warranty according to Project Floors NZ warranty conditions – www.projectfloors.co.nz			

Classification		Product composition	
	Utilization class 23 EN ISO 10874	1 Top element • PU-top layer with surface structure • decor paper • stabilisation	
	Utilization class 34 EN ISO 10874		Very heavy-duty use in the commercial sector
	Utilization class 43 EN ISO 10874		Heavy-duty use in the light industrial sector
	Scratch resistance EN 16776, annex A	2 Base layer ecuran high performance composite material	
	Anti slip category bfu R 9729		Utilization class 34 ≥ 6 N Utilization class 43 ≥ 7 N GS 1
	Anti slip category DIN 51130	3 Backing Integrated Fleece TEC-System	
	Staining and chemical resistance EN ISO 26987		Very good resistance according to the concentration and residence time
	Light fastness EN ISO 105-B02		~ 7
	Residual indentation EN ISO 24343-1		~ 0.05 mm
	Effect of a furniture leg EN 424		Foot type 0 – no visible change
	Castor chair test EN 425		25000 revolutions no damage with rolls type W
	Thermal resistance ISO 8302		~ 0.01 (m ² K)/W
	Impact sound reduction EN ISO 10140		~ 4 dB
	Dimension stability EN ISO 23999		~ 0.05 %
	Flexural behaviour EN ISO 24344		< 20 mm
REACH		free from SVHC substances ≥ 0.1 %	
Disposal		<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	



Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Project Floors NZ Ltd.

Project Floors (NZ) Limited - 27 Anvil Rd, Silverdale 0932, Auckland. PO Box 99, Silverdale 0944, Auckland, New Zealand

www.projectfloors.co.nz Ph: 09 4444 165 Email salesoffice@projectfloors.co.nz