

Easy Lay Vinyl Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS

EASY LAY LUXURY, HIGH PERFORMANCE PVC FLOOR COVERING FOR COMMERCIAL APPLICATION

TECHNICAL SPECIFICATIONS

m2/Box	1.8m2	Performance Class.	(EN685) 24, 34, 43 (K5)
Total Thickness	(EN428) 5.0mm	Wear Layer Thickness	0.55mm
Total Weight	(EN430) 8.7kg/m2	Residential indentation	0.05mm
Slip Resistance	R11	Behavior to Fire	B1
Colour Fastness	(DIN 53389) >6	Castor Chair Suitability	DIN 68131, Type W
Warranty	10 Year	Static Control	(DIN 51953) > 1010
Chemical Resistance	(DIN 51958) Present	Adhesive Recommendation	ProjectStik
		Impact Sound Improvement	ISO 10140-3 $\Delta L_W=8$ dB

REACTION-TO-FIRE PERFORMANCE COMPLIANCE

AREA OF BUILDING	MINIMUM CRITICAL RADIANT FLUX WHEN TESTED TO ISO 9239-1: 2010		
	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Easy Lay complies?
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m2	2.2 kW/m2	✓ 9.8 kW/m2
Exitways in all other buildings	2.2 kW/m2	2.2 kW/m2	✓ 9.8 kW/m2
Firecells accommodating more than 50 persons	2.2 kW/m2	1.2 kW/m2	✓ 9.8 kW/m2
Exitways in all other buildings	1.2 kW/m2	1.2 kW/m2	✓ 9.8 kW/m2

