

+ProTile Carpet Tile Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS

+Protile

BACKED BY EcoTX™

Construction	Level Loop & Multi-level loop	Pile Height	4.0mm (±0.5mm)
Yarn	Various 6.6 SDN Nylon	Backing	Next Generation EcoTX
Colour System	100% Solution Dyed	Tile Size	500 x 500 mm (5m2/box)
Gauge	1/12	Total Height	9 -10mm (±1.5mm)
Stitches	9 - 12 per inch	Flammability	Passed (GB 8624-2006)
Pile Weight	21 - 26 oz/yd2	Static Control	Life-of-the-carpet Static Protection
Recommended Adhesive	Specially formulated Project Floors ProjectStik3	Warranty	15 Year Product Warranty

REACTION-TO-FIRE PERFORMANCE COMPLIANCE

AREA OF BUILDING	MINIMUM CRITICAL RADIANT FLUX WHEN TESTED TO ISO 9239-1: 2010		
	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	EcoTX complies?
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m2	2.2 kW/m2	✓ 8.6 kW/m2
Exitways in all other buildings	2.2 kW/m2	2.2 kW/m2	✓ 8.6 kW/m2
Firecells accommodating more than 50 persons	2.2 kW/m2	1.2 kW/m2	✓ 8.6 kW/m2
Exitways in all other buildings	1.2 kW/m2	1.2 kW/m2	✓ 8.6 kW/m2

APPROVED INSTALLATION METHODS

