

# Go2Tile Carpet Tile Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS

## +Go2Tile™ CARPET TILES

### OUR MOST TRUSTED MODULAR FLOORING SOLUTION


Construction	Multi-level loop	Pile Height	2.5 - 6.0mm (±0.5mm)
Yarn	Invista Nylon 6	Backing	EuroBac or fibreglass Reinforced
Colour System	100% Solution Dyed	Tile Size	500 x 500 mm (5m <sup>2</sup> /box)
Gauge	1/12	Total Height	6 - 8mm (±1.5mm)
Stitches	10 per inch	Flammability	Passed (GB 8624-2006)
Pile Weight	21 oz/yd <sup>2</sup>	Static Control	Life-of-the-carpet Static Protection
Recommended Adhesive	Specially formulated Project Floors ProjectStik3	Area of Use	Heavy Commercial

### REACTION-TO-FIRE PERFORMANCE COMPLIANCE

AREA OF BUILDING	MINIMUM CRITICAL RADIANT FLUX WHEN TESTED TO ISO 9239-1: 2010		
	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Go2Tile complies?
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m <sup>2</sup>	2.2 kW/m <sup>2</sup>	✓ 5.0 kW/m <sup>2</sup>
Exitways in all other buildings	2.2 kW/m <sup>2</sup>	2.2 kW/m <sup>2</sup>	✓ 5.0 kW/m <sup>2</sup>
Firecells accommodating more than 50 persons	2.2 kW/m <sup>2</sup>	1.2 kW/m <sup>2</sup>	✓ 5.0 kW/m <sup>2</sup>
Exitways in all other buildings	1.2 kW/m <sup>2</sup>	1.2 kW/m <sup>2</sup>	✓ 5.0 kW/m <sup>2</sup>

## Go2Tile Carpet Tile Specifications

### PROJECT FLOORS (NZ) LTD SPECIFICATIONS



GREAT BARRIER 03



GREAT BARRIER 05



GREAT BARRIER 06



GREAT BARRIER 07



GREAT BARRIER 15



BLANKET BAY

We love your floor more than you do

#### APPROVED INSTALLATION METHODS

