

## Indoor, Outdoor Carpet Specifications

### PROJECT FLOORS (NZ) LTD SPECIFICATIONS

**KriActiv™**  
INDOOR / OUTDOOR CARPET

[www.projectfloors.co.nz](http://www.projectfloors.co.nz)

IDEAL FOR RETAIL, EDUCATION, HOSPITALITY & COMMERCIAL APPLICATIONS

TECHNICAL DATA	STANDARDS	INFO
Manufacturing Process	ISO 2424, DIN 61161	100% Solution Dyed Polypropylene Fibre
Country of Origin	Netherlands	
Roll Width	2m	
Surface Aspect		Various
Pile Yarn Composition	CEE 83/623	100% Polypropylene
Tuffs m2	ISO 163	-
Backing Lifetime Anti-static Warranty	ISO 2424	LF - Latex FR - Fire Retardant
Pile Height	ISO 1776, DIN 54325	See individual Specifications
Pile Weight	ISO 8543	See individual Specifications
Total Height	ISO 1765, DIN 53855	See individual Specifications
Total Weight	ISO 8543, DIN 53854	See individual Specifications
Fire Resistance	AS/NZS 1530.3:2004 AS/ISO 9239.1:2004	Spread of Flame (index 0 -10) 3 Smoke Developed (index 0 -10) 3 Average Critical Flux: 4.9kW/m2
Slip Resistance	Textile Flooring	> R11
Warranty	5 yr Indoor Limited	Waterproof, Rot-proof & Static
Thermal Retention	DIN 52612	0.17/0.15
UV Stabilised	Indoor Use	
Adhesive Recommendation	CarpetBond	

**Please refer to separate cleaning, maintenance and installation instructions**

Due to limitations in the manufacturing process, colour may vary slightly from batch to batch