



PROJECT FLOORS (NZ) LTD INFORMATION SHEET

DESCRIPTION

ProjectStik 3 is a solvent free, non-staining acrylic dispersion designed to provide a permanently tacky film for the installation of Project Floors Carpet Tiles.

SURFACE PREPARATION AND INSTALLATION

To be in accordance with

- NZS AS 1884:2013 Floor Coverings Resilient Sheet and Tiles
 Installation Practices.
- 2. The Australian Standard 2455.1:1995 Textile Floor Coverings Installation Practices.

All surfaces to be bonded shall be dry, permanently dry, level, smooth, sound and clean. Sub floors must also be free of wax, grease & hydrostatic pressure.

The minimum sub floor temperature before commencing surface preparation and adhesive application is 10°C.

It is recommended to prime all absorbent substrates with a suitable primer prior to application of adhesive.

All concrete substrate floors should be tested for moisture content according to the above AS/NZ Standard prior to undertaking surface priming or installation of flooring coverings.

TECHNICAL DATA

Appearance: Milky White Base: Acrylic

Flammability: Non-flammable (water based)

Toxicity: Non Toxic
Freezability: Avoid freezing

Tack-up: Typically 15-30 minutes (but may be longer) depending on temperature, floor absorbency,

humidity and application weights

COVERAGE

Approximately 5-8m2/litre depending on the condition and absorbency of the floor and the application method used.

APPLICATION

Adhesive should be applied with a 1.0mm - 1.5mm "V" notched trowel dependent on the porosity of the surface to be adhered to. Allow adhesive film to dry clear. The adhesive is now in a dry tack mode and the carpet tile may be placed in position. Best bonds will be achieved by placing the tiles into the adhesive as soon as possible after the film has cleared. It is not good practice to leave adhesive exposed to possible contaminants, such as dust, for long periods of time.

CLEAN UP

Any **ProjectStik 3** on the surface of floor coverings should be removed as soon as possible with a well dampened cloth. Once dry, the product is extremely tenacious and will trap dirt. Dried adhesive may be removed with Acetone.

Note: Before using any cleaner, first establish cleaner will not damage the carpet tile.

SHELF LIFE/STORAGE

12 months minimum on unopened containers stored between 5°C and 25°C. Keep in a well ventilated area away from direct heat sources and sunlight.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, DO NOT induce vomiting. Give a glass of water.

Material Safety Sheet available on request.

Enquiries should be directed to:

Project Floors (NZ) limited PO Box 99, Silverdale

Auckland

email: salesoffice@projectfloors.co.nz

Disclaimer: Information on this information sheet is, to the best available knowledge of the manufacturer, true and correct. However, owing to the diverse nature of the applications, conditions and materials used, no guarantee either expressed or implied can be given.