

TECHNICAL CHARACTERISTICS


PURLINE organic flooring | Purline 1500 | plank to glue
 Permanently elastic polyurethane flooring according to EN 16776
 free of chlorine, solvents and plasticizers



	wood XS	wood L	wood XL	stone XL	fusion XL
Format	600 x 100 mm	1200 x 200 mm	1500 x 250 mm	1000 x 500 mm	1000 x 500 mm
Product thickness	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm
Weight	3.9 kg/m ²	3.9 kg/m ²	3.9 kg/m²	3.9 kg/m ²	3.9 kg/m ²
Planks / m² per box	28 / 1.68 m ²	20 / 4.8 m ²	12 / 4.5 m²	10 / 5.00 m ²	10 / 5.00 m ²
Boxes / m² per pallet	144 / 241.92 m ²	48 / 230.40 m ²	52 / 234.00 m²	50 / 250.00 m ²	50 / 250.00 m ²
Warranty	10 years – Warranty according to Project Floors NZ warranty conditions – www.projectfloors.co.nz				



Classification		Product composition
	Utilization class 23 EN ISO 10874	1 Top element <ul style="list-style-type: none"> • PU-top layer with surface structure • decor paper • stabilisation
	Utilization class 34 EN ISO 10874	
	Utilization class 43 EN ISO 10874	
	Scratch resistance EN 16776, annex A	2 Base layer ecuran high performance composite material
	Anti slip category bfu R 9729	
	R9 Anti slip category DIN 51130	3 Backing Integrated Fleece TEC-System
	Staining and chemical resistance EN ISO 26987	
	Light fastness EN ISO 105-B02	
	Residual indentation EN ISO 24343-1	
	Effect of a furniture leg EN 424	
	Castor chair test EN 425	
	Thermal resistance ISO 8302	
	Impact sound reduction EN ISO 10140	
	Dimensions stability EN ISO 23999	
	Flexural behaviour EN ISO 24344	
	REACH	
	Disposal	



Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Project Floors NZ Ltd.