

Purline Cleaning and Maintenance

CLEANING AND MAINTENANCE GUIDE

PURLINE is given a very durable PU top layer at the factory. The PU top layer means the floor needs little care and reduces the maintenance costs over the long term. Any initial care or coating of the surface with polymer dispersions and the use of maintenance products are dispensed with!

Precautionary measures:

Sufficiently large textile carpet protection zones of at least 4 to 6 linear metres can reduce the dirt carried into the building by as much as 80%, thereby having a major effect on the life of the floor covering and cleaning costs.

Cleaning after installation:

Once the loose dirt lying on the floor covering has been removed, clinging dirt is removed manually or by machine. For mechanical dirt removal, red pads (3M pads) or soft brushes may be used. Water with the addition of a suitable PU cleaner may be used as a wiping solution. Initial care or coating after installation of the floor covering is not necessary.

Maintenance cleaning:

PURLINE is to be cleaned daily or at longer intervals as required. Loose dirt lying on it may be removed by sweeping, vacuum cleaning or damp wiping. Appropriate microfibre mop systems (e.g. Tronic or Ultra from Vermop) or impregnated non-woven cloths are suitable for damp wiping. In the event of heavy soiling with clinging dirt, a PU cleaner is added to the wiping water and the dirt is removed from the floor in a two-step wiping process. Alternatively a suitable scrubbing vacuum cleaner with a red cleaning pad or a soft scrubbing brush may be used. For disinfecting part of or the whole area, suitable disinfectants can be used. The products and methods used may need to be agreed with the hygiene officer responsible for the building. PURLINE has a very good resistance to transparent skin disinfectants.

Thorough cleaning:

Dispensed with!

Stain removal:

All staining and corrosive substances must be removed from PURLINE immediately.

When treating stains with cleaning agents or stain removers, a material compatibility test on an inconspicuous area or on an unglued flooring sample must first be conducted. The instructions and directions of the cleaning agent manufacturer must be observed.



Purline Cleaning and Maintenance

CLEANING AND MAINTENANCE GUIDE (2)

General instructions:

- After laying, the floor covering in areas with heavy traffic during the construction phase must be protected from damage with suitable protective coverings.
- Standing moisture under fittings is to be avoided.
- Table, chair and furniture legs are to be protected with suitable glides or protective mats.
- Use only appropriate chair and furniture castors in accordance with DIN EN 12529 (Type “W” – soft). Chair castors and chair and furniture glides are to be regularly maintained. The surfaces on which chair and furniture glides rest should be flat and rounded at the edges. Glides made of metal can become tarnished by moisture and cause stains.

Plant pots/tubs made of terracotta or clay can cause discoloration on elastic floor coverings. Please use suitable mats underneath these.

The compatibility of adhesive tapes on elastic floor coverings must be confirmed beforehand by the relevant manufacturer or queried by the user of the floor covering.

Coloured rubber or plastic glides and rollers as well as dark car, bicycle or transportation equipment tyres and other dyed materials can cause discoloration on elastic floor coverings. Please use light-coloured, migration-free furniture glides, rollers or tyres. Contact with dyed chemicals and other dyed substances should be avoided as a matter of principle or these should be removed from the floor covering surface as soon as possible in case of contact.

- Heavy localised loads on a small standing area, which also applies to stiletto heels or high-heeled shoes, for example, may lead to irreversible marks in or damage to resilient floorings. If necessary use suitable and sufficient dimensional protective mats to spread the load.
- The anti-slip quality and traction of floorings is affected considerably by dirt carried in, the frequency of cleaning and the cleaning and care products that are used.
- Please use only the compatible cleaning agents/care products of one manufacturer. Scouring powders, sanitary facility cleaners, acids and strong solvents may lead to damage to the floor covering surface.
- Coloured wound and skin disinfectants as well as hair dyes or bleach containing peroxide can cause irreversible discoloration. If there is any uncertainty surrounding the use of chemical, colouring substances or foods, a resistance test should first be carried out on an inconspicuous area of the floor or on an uninstalled piece of floor. In case of doubt, please contact our service hotline.

Waste disposal:

Private waste disposal: like laminated pieces of furniture; possible with normal household waste / bulk waste

Commercial waste disposal: waste disposal code AVV 170203