



Purline Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS

Wear class according to EN 14565	EN 685/EN IOS 10874	24, 34, 43
Total thickness	EN 428/EN ISO 24346	2.5mm
Weight EN 430/EN ISO 23997	Roll: 3.6kg/m ²	20Lm roll: 144kg
Residual indentation EN 433/EN ISO 24343-1	Roll: 0.05mm	
Dimensional Stability EN 434/ISO 23999	Roll: ≤ 0.05%	
Bending Behaviour	EN435/ISO 24344	<20mm
Wear Behaviour	EN 660-2	Group T
Anti-slip friction coefficient	DIN 51130	R9
Slip resistance EN 13893		DS (> 0.3)
Reaction to fire	EN 13501-1	Cfl-s1 highly flame resistant
Light fastness	EN ISO 105-B02	≥7
Underfloor Heating	Suitable for all standard hot water underfloor systems	
Thermal resistance	ISO 8302	0.01 m ² K/W
Resistance to castor chairs	EN 425/ISO 4918	Typ W
Impact Sound Improvement	EN ISO 10140	4 dB
Chemical resistance	EN423/ISO 26987	Very good resistance depending on concentration and exposure time
Warranty	10 years	
Furniture leg test	EN 424	No visible damage
Antistatic properties	EN 1815	≤ 2 kV

Please refer to separate cleaning, maintenance and installation instructions

20m long 2m wide roll (40m²/roll)

