

# PROJECT FLOORS

## Queen Street

### + Profile BACKED BY EcoTX™

### TECHNICAL SPECIFICATIONS

Construction	Loop Pile Tip Sheared	Pile Height	3.5mm / 8.0mm
Yarn	BCF	Backing	StableShield
Colour System	100% Nylon(polyamide 6)	Tile Size	25 cm x 100 cm
Gauge	1-10"	Area of Use	Heavy Commercial
Stitches	9 - 12 per inch	Flammability	Passed (GB 8624-2006)
Pile Weight	850 g/m2	Static Control	Life-of-the-carpet Static Protection

### REACTION-TO-FIRE PERFORMANCE COMPLIANCE

AREA OF BUILDING	MINIMUM CRITICAL RADIANT FLUX WHEN TESTED TO ISO 9239-1: 2010		
	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	EcoTX complies?
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m2	2.2 kW/m2	✓ 8.6 kW/m2
Exitways in all other buildings	2.2 kW/m2	2.2 kW/m2	✓ 8.6 kW/m2
Firecells accommodating more than 50 persons	2.2 kW/m2	1.2 kW/m2	✓ 8.6 kW/m2
Exitways in all other buildings	1.2 kW/m2	1.2 kW/m2	✓ 8.6 kW/m2

