

## Residential Vinyl Specifications

### PROJECT FLOORS (NZ) LTD SPECIFICATIONS

LUXURY, HIGH PERFORMANCE PVC FLOOR COVERING FOR COMMERCIAL APPLICATION

Covering type according to DIN 16951	Heterogeneous Plankwood	Heterogeneous Tiles
Packaging per box	3.34m2 **	3.34m2 **
Performance classification EN 685	21, 23, 31	21, 23, 31
Total thickness EN 428	2.0mm	2.0mm
Wear layer thickness EN 429	0.55mm	0.55mm
Surface Treatment	Yes/PU	Yes/PU
Residual indentation EN 433	0.05mm	0.05mm
Caster chair suitability EN 425	Suitable for castor chairs in accordance with DIN 68131 Type W	Suitable for castor chairs in accordance with DIN 68131 Type W
Behaviour to fire DIN 4102	B1	B1
Impact sound improvement DIN 52210	4dB	4dB
Colour fastness DIN 53389	> 6	> 6
Electrostatic characteristics DIN 51953	> 1010	> 1010
Chemical resistance DIN 51958	Present	Present
Slip resistance	R11	R11
Adhesive recommendation	ProjectBond	ProjectBond

**Please refer to separate cleaning, maintenance and installation instructions**

\*\* @home Range 3.37m2/box

