

PROJECT FLOORS (NZ) LTD TECHNICAL INFORMATION

ProFloor Sealer is a stain resistant floor sealer for use on all internal resilient floors such as vinyl, rubber and porous composite tiles. ProFloor Sealer is a semi permanent sealer that enhances the appearance of old floors when used with a Project Floors finish according to directions.

FEATURES AND BENEFITS

- ProFloor Sealer is a semi-permanent floor sealer designed to provide a base for resilient floors.
- ProFloor Sealer seals and protects against a wide range of damaging and staining substances.
- Coverage: 1 litre approx. 30-40m².
- ProFloor Sealer resists most common types of floor spills providing greater floor protection.
- It will not discolour over time.
- ProFloor Sealer is ideally suited to selective stripping programs.

PRODUCT USAGE

Directions for Use:

APPLICATION

- Strip old coatings using ProFloor Stripper according to label directions. Allow floor to dry.
- Apply 2-3 coats of ProFloor Sealer using a clean mop or applicator.
- Allow coat to dry for 30-40 minutes depending on drying conditions.
- Apply 2-4 further coats of ProFloor Sealer as required.

PROFLOOR SEALER REMOVAL

- Use ProFloor Stripper diluted 1:4 in cool water with a 7-10 minute contact time. Re-wet with additional stripper solution.
- Scrub thoroughly with a brush or aggressive pad. If coats are heavy, a second strip may be required.
- Re-apply coats of ProFloor Sealer using a clean mop or applicator.
- Apply 2-4 further coats of Project Floors Sealer as required.

First Aid

In case of contact with eyes rinse thoroughly with large quantities of water for at least 15 minutes. If swallowed do not induce vomiting. Drink milk or water. Seek medical attention.

See Material Safety Data Sheet for further information.

Approvals

Slip Classification: Class F AS/NZ5 4586:1999NZFSA approved C25 (all animal products except dairy)

24 HOUR EMERGENCY RESPONSE

Within New Zealand 0800 CHEMCALL or 0800 243 622