

Commercial Vinyl Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS

LUXURY, HIGH PERFORMANCE PVC FLOOR COVERING FOR COMMERCIAL APPLICATION

Covering type according to DIN 16951	Heterogeneous Plankwood	Heterogeneous Tiles
Packaging per box	3.34m2 **	3.34m2 **
Performance classification EN 685	24, 34, 43 (K5)	24, 34, 43 (K5)
Total thickness EN 428	2.0mm	2.0mm
Wear layer thickness EN 429	0.5 - 0.8mm	0.5 - 0.8mm
Total weight EN 430	4.8kg/m2	4.8kg/m2
Residual indentation EN 433	0.05mm	0.05mm
Caster chair suitability EN 425	Suitable for castor chairs in accordance with DIN 68131 Type W	Suitable for castor chairs in accordance with DIN 68131 Type W
Behaviour to fire DIN 4102	B1	B1
Impact sound improvement DIN 52210	4dB	4dB
Colour fastness DIN 53389	> 6	> 6
Electrostatic characteristics DIN 51953	> 1010	> 1010
Chemical resistance DIN 51958	Present	Present
Slip resistance	R11	R11
Adhesive Recommended	ProjectBond Adhesive	ProjectBond Adhesive

Please refer to separate cleaning, maintenance and installation instructions

