



## PROJECT FLOORS (NZ) LTD SPECIFICATIONS

# Thrive<sup>®</sup> ProTile

World's First Carbon Negative Fibre with EcoTX™ acoustic backing

Construction	Level Loop & Multi-level loop	Pile Height	4.0mm (±0.5mm)
Yarn	Thrive <sup>®</sup> matter Nylon 6 fibre	Backing	Next Generation EcoTX
Colour System	100% Solution Dyed	Tile Size	1000 x 330 mm (4.995m <sup>2</sup> /box)
Gauge	1/12	Total Height	9 -10mm (±1.5mm)
Stitches	9 - 12 per inch	Flammability	Passed (GB 8624-2006)
Pile Weight	21 - 26 oz/yd <sup>2</sup>	Static Control	Life-of-the-carpet Static Protection
Recommended Adhesive	Specially formulated Project Floors ProjectStik	Warranty	15 Year Product Warranty

## REACTION-TO-FIRE PERFORMANCE COMPLIANCE

AREA OF BUILDING	MINIMUM CRITICAL RADIANT FLUX WHEN TESTED TO ISO 9239-1: 2010		
	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Thrive <sup>®</sup> complies?
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m <sup>2</sup>	2.2 kW/m <sup>2</sup>	✓ 8.6 kW/m <sup>2</sup>
Exitways in all other buildings	2.2 kW/m <sup>2</sup>	2.2 kW/m <sup>2</sup>	✓ 8.6 kW/m <sup>2</sup>
Firecells accommodating more than 50 persons	2.2 kW/m <sup>2</sup>	1.2 kW/m <sup>2</sup>	✓ 8.6 kW/m <sup>2</sup>
Exitways in all other buildings	1.2 kW/m <sup>2</sup>	1.2 kW/m <sup>2</sup>	✓ 8.6 kW/m <sup>2</sup>