

Indoor, Outdoor Carpet Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS

σ Velcord™

INDOOR / OUTDOOR CARPET

IDEAL FOR RETAIL, EDUCATION, HOSPITALITY & COMMERCIAL APPLICATIONS

www.projectfloors.co.nz

TECHNICAL DATA	STANDARDS	INFO
Manufacturing Process	ISO 2424, DIN 61161	100% Solution Dyed Polypropylene Fibre
Country of Origin	Netherlands	
Roll Width	2m	
Surface Aspect		Heavy Ribbed
Pile Yarn Composition	CEE 83/623	100% Polypropylene
Tuffs m2	ISO 163	-
Backing Lifetime Anti-static Warranty	ISO 2424	LF - Latex FR - Fire Retardant
Pile Height	ISO 1776, DIN 54325	4.0mm +/- 7.5%
Pile Weight	ISO 8543	1105 g/m2 +/- 7.5%
Total Height	ISO 1765, DIN 53855	8.2mm +/- 7.5%
Total Weight	ISO 8543, DIN 53854	LF - 1590g/m2
Fire Resistance	AS/NZS 1530.3:2004 AS/ISO 9239.1:2004	Spread of Flame (index 0 -10) 3 Smoke Developed (index 0 -10) 3 Average Critical Flux: 4.9kW/m2
Moisture Absorbtion	0.0006%	Will not rot or smell
Slip Resistance	Textile Flooring	> R11
Warranty	10 yr Indoor Limited	Waterproof, Rot-proof & Static
Thermal Retention	DIN 52612	0.17/0.15
UV Stabilised	Indoor Use	
Adhesive Recommendation	CarpetBond	

Please refer to separate cleaning, maintenance and installation instructions

Due to limitations in the manufacturing process, colour may vary slightly from batch to batch