

+ProTile Carpet Tile Specifications

PROJECT FLOORS (NZ) LTD SPECIFICATIONS + **ProTile**
BACKED BY EcoTX™

+ Waitakere™

Construction	Multi-level loop - Tip Sheared	Pile Height	4.5mm (±0.5mm)
Yarn	6.6 SDN Nylon	Backing	Fibreglass Reinforced
Colour System	100% Solution Dyed	Tile Plank Size	1000 x 250 mm (4m ² /box)
Gauge	1/10	Total Height	8mm (±0.5mm)
Stitches	9 per inch	Flammability	Passed (GB 8624-2006)
Pile Weight	31 oz/yd ² (Stone 32 oz/yd ²)	Static Control	Life-of-the-carpet Static Protection
Recommended Adhesive	Specially formulated Project Floors ProjectStik3	Warranty	15 Year Product Warranty

REACTION-TO-FIRE PERFORMANCE COMPLIANCE

AREA OF BUILDING	MINIMUM CRITICAL RADIANT FLUX WHEN TESTED TO ISO 9239-1: 2010		
	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Waitakere complies?
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²	✓ 5.0 kW/m ²
Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²	✓ 5.0 kW/m ²
Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²	✓ 5.0 kW/m ²
Exitways in all other buildings	1.2 kW/m ²	1.2 kW/m ²	✓ 5.0 kW/m ²

APPROVED INSTALLATION METHODS

