

Dropsafe®

Drops prevention devices

Test Certificate

This Dropsafe® product has been tested and is fully compliant with the stated SWL.

Test Description	Test Report No.	
Carabiner SUS316 Tension Test	SGS	HKHL1303022510SD 16/04/13
Choke Plate SUS316 Linear Pull Test	SGS	HKHL1411081297SD 06/03/2015
Choke Plate SUS316 Loop Pull Test	SGS	HKHL1411081298SD 06/03/2015
Securing Cable SUS316 with Copper Ferrule Pull Test	SGS	HKHL1305043959SD-01 31/05/13
Mesh Wire Rope SUS316 1.5mm Pull Test	SGS	HKHL1305043960SD-01 31/05/13
Mesh Clip SUS316 Perpendicular Pull Test	SGS	HKHL1305043950SD-01 31/05/13
Assembled Product SUS316	SGS	HKHL1304028232SD 16/04/13
Last periodic assembly inspection for this model	SGS	SZXWT00702814 07/08/13
Components Pull Test at 500°C	ADDA	121214AD 06/01/2015
Components Pull Test at -40°C	ADDA	121215AD 06/01/2015

Batch No:

QC:

Vessel / Facility Name:

Installation Location:

Installed by:

Purchase Date:


Replacement Date:

Product Specification:

Dropsafe® Model #: 7500720

SWL: 4 Kg (8.8 lbs)

DropSafe Mesh Safety Cover
00720, 2212182



A = 220 mm (8.5")
B = 140 mm (5.5")
C = 90 mm (3.5")

Product fits over fixture this way

Fixture mounting configuration: Vertical

Product should be replaced 36 months after purchase