FISHER!

Product Specification



Lead Time:

Customer: AR Valve Resources Ltd Contact: Contact: Ben Rowland Customer Reference: Sales Office Reference:

tom 4

Item: 1 Rev: Qty: 10

Tags: Date Last Modified: 20/01/2021

Description: NPS 1/2 67DFSR-24

Service Description:

Body Tapping(inlet/outlet): None

Orifice/Port: 3/8

Pressure Registration: Internal

Trim Material: SST

Gauge, Tire Valve or Pipe Plug Material: Not App

Spring Case Tapping: 1/4 NPT Spring Part Number: T14114 Vent Location: Over Inlet Max Inlet Pressure: 250 psig Max Outlet Pressure: 60 psig

Approximate Shipping Weight(each): 4.6 lbs (2.09 kg)

Supplemental Attribute: Not App

Pressure: Temperature:

Offset: see Flow Data

Flowing Drop: Shutoff Drop:

World Area Selections: Europe

Direct Operated Regulator:

Type: 67DFSR
Service: Std
Internal Relief: Yes
Spring Range: 0 to 60 psi

Temperature Range: -40 to 180 Deg F

Disk/Seat Material: SST/NBR Diaphragm Material: NBR Filter Material: UHMWPE 5 Micron

Filter Drain: SST Drain

Adjusting Screw/Handwheel: Adjusting Screw with Closing Cap

Gauge, Tire Valve or Pipe Plug: None

Panel Mounting: None

Bleed: None

ATEX for Regulators: **No** Valve Size: **NPS 1/2** Body Material: **CF3M/CF8M**

Rating: **Not App**End Connection: **NPT**BWE Schedule: **Not App**