

Jet Pumps

Cast Iron Convertible Jet Pumps With Power Plus 56 Frame Motor

SPECIFICATIONS

- Sturdy cast iron construction.
- Highly serviceable NEMA J or NEMA J adaptable motor.
- Includes pressure switch.
- Thermal overload protects against overheating.
- Ejector purchased separately.



Convertible Jet Pumps with NEMA J adaptable uni-frame motor

NE462 - 1/2 HP 115/230 V 1-1/4" inlet, 3/4" discharge

NE463 - 1 HP 115/230 V 1-1/4" inlet, 1" discharge

MODEL	SUCTION LIFT FT.	PRESSURE SWITCH SETTING PSI	CAPACITIES GPM AT DISCHARGE PRESSURE PSIG				SUCTION & DISCHARGE	PUMP SHIPPING WEIGHT (LB)
			20	30	40	50		
460-0006 1/2 HP NE460	5	30-50	11.6	11.0	9.8	7.0	1-1/4" x 3/4"	40
	15		9.0	8.8	8.0	5.6		
	25		5.6	5.6	5.5	4.5		
461-0006 3/4 HP NE461	5	30-50	17.5	17.0	15.0	10.0	1-1/4" x 3/4"	42
	15		13.0	12.9	12.5	8.0		
	25		8.0	7.8	7.5	5.5		

Shallow And Deep Well Capacities With Convertible Ejectors

PUMP MODEL	EJECTOR MODEL	DISCHARGE PRESSURE PSI	CAPACITIES IN GPM FROM PUMP TO PUMPING WATER LEVEL IN FEET													DW MINIMUM OPERATING PRESSURE PSI		
			SW EJECTOR ATTACHED TO PUMP			DEEP WELL EJECTOR IN 4" ID WELL												
			5	15	25	20	30	40	50	60	70	80	90	100	110			
462-0006 1/2 HP NE462	10-2353	20	11.3	8.7	5.3													--
		40	9.5	7.8	5.2													20
	10-2355	20	10.2	8.0	4.8	11.7	8.3	7.0										
40		9.7	7.3	4.5	6.0	4.7	3.8											30
10-2356	20						6.7	6.0	5.3	4.3	3.3	2.5						30
	40						4.3	3.8	3.3	2.5	1.7	0.8						30
463-0006 1 HP NE463	10-2357	30	15.7	12.3	8.3	16.7	14.2	12.2	8.3									35-37
		50	15.0	12.2	8.0	12.5	8.3	5.0	2.5									35-37
	10-2355	30	10.0	7.5	4.7	11.7	11.7	11.5	10.3	9.0	7.7	6.2	4.8					37-39
		50	9.5	7.3	4.3	9.2	9.2	8.2	7.0	5.7	4.3	3.2	1.7					37-39
10-2358	30											5.0	4.8	4.3	3.7			39
	50											3.7	3.3	3.0	2.7			39
10-2354	20	17.2	12.8	7.7														--
	40	14.8	12.2	7.2														--


NOTE: See installation instructions for setting flow control for maximum pressures.

Reduce your stock keeping units with Zoeller mix and match tank fitting packages

Add:

- 10-2367 compact Air-E-Tainer®
- 10-2381 fittings package
- Zoeller Shallow Well Jet Pump

And get: Cottage Air-E-Tainer® System



Add:

- 10-2368 or 10-2369 vertical bottom connect
- Air-E-Tainer®
- 10-2373 fittings package
- Zoeller Convertible Jet Pump

And get: Top mounted vertical Air-E-Tainer® Systems bottom connect

