

# RACK SPECIFICATIONS

## DirectConnect Assembled Wall Mount Racks

### Assembled Wall Mount Racks

all measurements in mm



#### DCRMW6U

#### DCRMW12U

Tinted Front Glass Door	Tinted Front Glass Door
Wall Hinge for Easy Access	Wall Hinge for Easy Access
Lock and Key for Security	Lock and Key for Security
Ventilation Slots for Cooling	Ventilation Slots for Cooling
Removable Side Panels	Removable Side Panels
Two Easy Access Wire Channels	Two Easy Access Wire Channels
Standard Rack Spacing for Mounting Equipment	Standard Rack Spacing for Mounting Equipment
Dimensions: 600 L x 600 W x 371mm H	Dimensions: 600 L x 600 W x 638mm H
Box Dimensions: 603 L x 635 W x 683 H	Box Dimensions: 603 L x 635 W x 683 H
Max Load: 41 kg.	Max Load: 54 kg.

### Floor-Standing Racks



- 4-Non-Marking Castors
- 4-Adjustable Stabilizing Feet
- 1-Tinted Locking Glass Door
- 1-Locking Rear Door- No Glass
- Front/Rear Set Keys
- Removable Side Panels
- 2-Easy Access Wire Channels

#### DCRM42U

9-2U Vented Shelves  
 9-2U Vented Blanks  
 600L x 600W x 2058H  
 Max Load: 499 kg.

#### DCRM12U

#### DCRM18U

#### DCRM27U

#### DCRM38U

2- 2U Vented Shelves	3- 2U Vented Shelves	5- 2U Vented Shelves	7-2U Vented Shelves
2- 2U Vented Blanks	3- 2U Vented Blanks	5- 2U Vented Blanks	7-2U Vented Blanks
600L x 600W x 723H	600L x 600W x 991H	600L x 600W x 1398H	600L x 600W x 1880H
Max Load: 136 kg.	Max Load: 226 kg.	Max Load 340 kg	Max Load: 476 kg

# OPEN RACKS SPECIFICATIONS

## Open Racks

all measurements in mm



**DCOR12U**

4ea Non-Marking Casters
4ea Stabilizing Feet
Vented Black Bars
4ea Threaded Rails
508L x 502W x 693H



**DCOR18U**

4ea Non-Marking Casters
4ea Stabilizing Feet
Vented Black Bars
4ea Threaded Rails
508L x 502W x 960H



**DCOR27U**

4ea Non-Marking Casters
4ea Stabilizing Feet
Vented Black Bars
4ea Threaded Rails
508L x 5025W x 1360H

**DCOR38U**

4ea Non-Marking Casters
4ea Stabilizing Feet
Vented Black Bars
4ea Threaded Rails
508L x 502W x 1849H

**DCOR42U**

4ea Non-Marking Casters
4ea Stabilizing Feet
Vented Black Bars
4ea Threaded Rails
508L x 502W x 2027H