



Muro™ Series

On-wall Speakers

When space is at a premium and performance is top of mind, the compact proportions of the Muro Series make on-wall installation a breeze. Bring huge dimensionality to your system with a speaker that makes itself heard but barely seen.



ELAC has achieved numerous industry accolades for engineering and sonic performance for floorstanding and bookshelf speaker design. Our engineering team used the same techniques and high standards to design the Muro™ Series on-wall products.

MURO™ SERIES ON-WALL SPEAKERS

Silk Dome Tweeter With Deep Spheroid Waveguide

The waveguide surrounding the new ELAC high-frequency driver features a custom, deep spheroid profile to improve directivity control and efficiency.

Custom-designed woofer with aluminum cones

Aluminum cones offers a superior strength-to-weight ratio and improved damping characteristics over conventional paper or plastic drivers. This added strength means arriving at designs that achieve a broader bandwidth with smoother response.

AXIS Tilt Control (OW-V41L Model Only)

Allows for the listening axis to be directed towards the listener based on mounting orientation and height. Selectable by a rear panel switch.

Intricate Crossover

A custom multi-element crossover with audio-grade components is implemented to ensure smooth transition between the drivers

Painted Baffle

A satin black or white painted baffle gives the Muro On-Wall speakers a luxurious look to fit into practically any decor.

Flexible Mounting Options

Both Muro On-wall allow for both vertical and horizontal mounting.



SPECIFICATIONS	OW-V41S	OW-V41L
	On-wall Muro 4-inch Surround Speaker	On-wall Muro Dual 4-inch LCR Speaker
Enclosure Type	2-way passive radiator, sealed	2-way dual passive radiator, sealed
Tweeter	1-inch soft dome	1-inch soft dome
Woofer	4-inch Aluminum cone	Dual 4-inch Aluminum cones
Passive Woofer	4-inch Aluminum cone	Dual 4-inch Aluminum cones
Crossover Frequency	2,800 Hz	2,800 Hz
Frequency Response	75 to 35,000 Hz	75 to 35,000 Hz
Sensitivity	86 db at 2.83 v/1m	86 db at 2.83 v/1m
Max Power Input	80 watts	80 watts
Nominal impedance	6 Ohm	8 Ohm
Binding Posts	5-way metal	5-way metal
Cabinet	CARB2 rated MDF	CARB2 rated MDF
Cabinet Finish	Painted Satin Black or White Front Baffle with vinyl wrapped cabinet	Painted Satin Black or White Front Baffle with vinyl wrapped cabinet
Grill	Magnetic Grey or Black Fabric Grill	Magnetic Grey or Black Fabric Grill
Accessories Included	Mounting template, manual	Mounting template, manual
Orientation Crossover Switch	No	Yes
Dimensions (WxHxD)	7.81 in / 198 mm x 15.69 in / 399 mm x 3.38 mm / 86 mm	7.81 in / 198 mm x 25.50 in / 648 mm x 3.38 in / 86 mm
Weight	9.92 lbs / 4.50 kg	15.43 lbs / 7.00 kg