


EL-SC-300-ZW 

ELAN[®]

System Controller with Z-Wave



A Flagship Controller for Your Most Demanding Installations

The EL-SC-300-ZW is the premium control center for the connected home. It brings together all your intelligent devices and allows them to work together in one seamless system. Control media, lighting, climate, pool/spa, irrigation, and more through a single app interface.

The EL-SC-300-ZW is the flagship ELAN[®] controller for your most demanding installations. With options for RS-232, RS-485, Relays, IR, IP, input sensors, and Z-Wave control, the EL-SC-300-ZW gives you the ultimate flexibility for a system of virtually any size.



EL-SC-300-ZW

System Controller with Z-Wave

ORDER NO. EL-SC-300-ZW



FEATURES

- **Compatibility** – Control all of your devices, no matter what the format. Integrated IP, serial, and infrared control in a one-box design
- **Multi-platform Experience** - Themes and layouts will be consistent across all devices, whether you're using the ELAN® Touch Panels or Mobile or Desktop Apps.
- **Z-WAVE® Integration** - Included Z-Wave functionality enables control and automation of compatible Z-Wave devices.
- **OSD** - Connection for OSD to control your ELAN system from any display.
- **Audio Output** - Allows video doorbells to play chimes throughout the home audio system
- **PoE Ready** – With Power over ethernet capability built in you can utilize your wired network setup to reduce the amount of cables needed.
- **Powerful** -The EL-SC-300-ZW packs amazing punch into a single rack space; rack mount hardware included.
- **A great partner** – Pair with the EL-IO-200 Control Extender on larger or decentralized installations.



| CONNECTIONS | |
|------------------------|--|
| RS-232 | (8) RJ-45 ports. Null modem configurable |
| RS-485 | (2) RJ-45 ports |
| IR Output | (12) 3.5mm ports. (Mono), - 12V DC |
| Signal Input | (4) Terminal Block Connectors 3-pin |
| Relay | (6) Terminal Block Connectors 3-pin |
| HDMI | (1) For on-screen display 1.4b |
| USB | (1) 3.0 USB / (1) 2.0 USB |
| RCA Audio | (2) Stereo audio out |
| Ethernet | (1) RJ-45 port |
| Wi-Fi | 2.4 / 5 GHz 802.11 b/g/n/ac |
| SYSTEM | |
| Software Compatibility | Requires Core Module 8.6 or above |
| Updates | Managed by Core Module Software |
| GENERAL | |
| Power | 120/240VAC Input 12VDC 1A output PoE IEEE 802.3af (802.3at Type 1) |
| Operating Temperature | 0° to 40° C |
| Operating Humidity | 90% Maximum (Non-Condensing) |
| Mounting | Free standing, Rack mount |
| Product Dimensions | With feet: 17" W x 2.25" H x 14" D (431.8mm W x 57.2mm H x 355.6mm D) Without feet, with rack mount brackets: 19" W x 1.75" H x 14" D (482.6mm W x 44.45mm H x 355.6mm D) |
| Weight | 8 lbs, 11oz / 3.95kg |
| Z-WAVE TRANSCEIVER | |
| Frequency Band | Region Allocated 919-921MHz for NZ/AU |
| RZ-Wave | 700 Series |
| Supported Regions | Multi-Region |
| Connection | USB / ELAN Controller |
| Power Consumption | 5V |
| Power Connection | USB / ELAN Controller |
| Operating Temperature | 32° to 104°F / 0° to 40°C |
| Operating Humidity | 90% Maximum (Non-Condensing) |
| Product Dimensions | 1.5w x 1.5h x .5d in. / 40w x 40h x 17d mm |
| Connector Cable Length | 6.5 feet / 2 meters |



elancontrolsystems.com