



K  
O  
O  
B  
W  
E

**SpeakerCraft**



**This Is What We Did Change.**

**A SpeakerCraft Design May Change.**

**What Makes It SpeakerCraft Never Will.**

Today, computers, televisions, telephones and other technology-driven products are as much of a fashion statement as they are pieces of ground breaking technology. Which is why Speakercraft is pleased to show you our latest thinking on the subject which we call Profile.



*Profile AIM8*

Profile is a line of Speakercraft's best selling ceiling and inwall speakers with a small but significant twist. A sort of variation on a theme. Each Profile speaker



# SpeakerCraft

**This Is What We Didn't.**

starts out as an exact technical clone of one of our AIM, CRS or AIM LCR speakers. But then we add a beautiful, more 'customized' look with no bezel and a smart and invisible mounting flange. The result is a line of field-proven, award-winning speakers with a whole new set of party clothes.

For example, take the newest addition to the Profile line: the Profile AIM7 MT

inwall speaker. It's highlighted by Profile's signature flangeless facade along with a 7"



Aluminum Cone Woofer, Pivoting 1" Aluminum Dome Tweeter and a good deal more.

The dramatically new Profile speaker line from SpeakerCraft. Don't let their svelte lines fool you. Each is truly a wolf in sheep's clothing and available today!



*AIM7 MT*

*Profile*<sup>™</sup>  
**SpeakerCraft**<sup>®</sup>

# Profile Speakers

Contents	Page
AIM In-Ceiling	6
CRS In-Ceiling	8
DT In-Ceiling	10
AccuFit In-Ceiling	10
AIM Cinema In-Wall	11
AIM LCR In-Wall	12
MT In-Wall	13

# Profile

---

Visually, Flawless. Sonically, Perfect.



## THE SOUND

Music is an aural experience that transcends our other four senses. It pervades our thoughts and fills our souls. The soundtrack in a film has the same effect. It enhances the images and dramatically transforms the experience. SpeakerCraft has been producing loudspeakers for the past three decades that allow the listener to be immersed in sound and substance. The Profile series continues this tradition with realism and dynamics that deliver every nuance the original artists intended.

## THE LOOK

All of this impressive sonic performance is only valuable if the loudspeaker is attractive enough to live in the space where the music will be enjoyed. Having created and manufactured the first in-wall speakers for residential applications, we understand how important the speaker's appearance is to the homeowner. Once again, the Profile series delivers. Almost invisible subtlety. A flawless look.

## THE EXECUTION

Through precise engineering and with the use of Neodymium magnets, the Profile series is little more than a shadow on the wall or ceiling. Although there is still a flange to cover the rough edge of the drywall after the hole has been cut, the final appearance is all grille with only the slightest edge to create a smooth, finished result.



Profile Square Grilles Available

*Profile*<sup>™</sup>



## Profile AIM8 Five

- Flangeless Appearance
- Pivoting 8" Kevlar® Woofer
- Pivoting 1" Aluminum/Magnesium Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Accu-Grille Technology
- Timbre-Matched to All Five Series

- Sensitivity: 91dB 1W/1m
- Power Handling: 150 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 33Hz - 20kHz
- Diameter x Depth: 11" x 5 3/4"  
279 mm x 146 mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248 mm)



## Profile AIM8 Three

- Flangeless Appearance
- Pivoting 8" Aluminum Woofer
- Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Accu-Grille Technology
- Timbre-Matched to All Three Series

- Sensitivity: 89dB 1W/1m
- Power Handling: 150 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 37Hz - 20kHz
- Diameter x Depth: 11" x 5 3/4"  
279 mm x 146 mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248 mm)



## Profile AIM8 Two

- Flangeless Appearance
- Pivoting 8" Resin Reinforced Fiberglass Woofer
- Pivoting 1" Treated Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Accu-Grille Technology
- Timbre-Matched to All Two Series

- Sensitivity: 89dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11" x 5 3/4"  
279 mm x 146 mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248 mm)



## Profile AIM8 One

- Flangeless Appearance
- Pivoting 8" Polypropylene Woofer
- Pivoting 1" Treated Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All One Series
- Sensitivity: 88dB 1W/1m

- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11" x 5 3/4"  
279 mm x 146 mm (with Grille)
- Cut-Out Diameter: 9 3/4" (248 mm)



### Profile AIM7 Five

- Flangeless Appearance
- Pivoting 7" Kevlar® Woofer
- Pivoting 1" Aluminum/Magnesium Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 91dB 1W/1m

- Power Handling: 150 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 35Hz - 20kHz
- Diameter x Depth: 9 5/8" x 5 1/2"  
244 mm x 130 mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210 mm)



### Profile AIM7 Three

- Flangeless Appearance
- Pivoting 7" Aluminum Woofer
- Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 91dB 1W/1m

- Power Handling: 125 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9 5/8" x 5 1/2"  
244 mm x 130 mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210 mm)



### Profile AIM7 Two

- Flangeless Appearance
- Pivoting 7" Resin Reinforced Fiberglass Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m

- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9 5/8" x 5 1/2"  
244 mm x 130 mm (with Grille)
- Cut-Out Diameter: 8 1/4" (210 mm)



## Profile AIM5 Three

- Flangeless Appearance
- Pivoting 5¼" Aluminum Woofer
- Pivoting ¾" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 89dB 1W/1m
- Power Handling: 100 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 50Hz - 20kHz
- Diameter x Depth: 8" x 4½"  
203 mm x 114 mm (with Grille)
- Cut-Out Diameter: 6⅝" (168 mm)



## Profile AIM5 One

- Flangeless Appearance
- Pivoting 5¼" Polypropylene Woofer
- Pivoting ¾" Treated Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All One Series
- Sensitivity: 88dB 1W/1m
- Power Handling: 75 Watts
- Impedance: 8 Ohm
- Frequency Response: 55Hz - 20kHz
- Diameter x Depth: 8" x 4½"  
203 mm x 114 mm (with Grille)
- Cut-Out Diameter: 6⅝" (168 mm)



## Profile A6

- Flangeless Appearance
- 6½" Polypropylene Woofer with Rubber Surround
- Pivoting 1" Silk Tweeter
- Woofer and Tweeter Baffle Fixed at 15 Degrees
- Sensitivity: 92dB 1W/1m
- Power Handling: 100 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9¼" x 4⅝"  
235 mm x 117 mm (with Grille)
- Cut-Out Diameter: 8¼" (210 mm)





### Profile CRS8 Three

- Flangeless Appearance
- 8" Aluminum Woofer
- Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m
- Power Handling: 125 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 38Hz - 20kHz
- Diameter x Depth: 11½" x 4½"
- 303 mm x 114 mm (with Grille)
- Cut-Out Diameter: 9¾" (248 mm)



### Profile CRS8 Two

- Flangeless Appearance
- 8" Glass Composite Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m
- Power Handling: 1200Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11½" x 4½"
- 303 mm x 114 mm (with Grille)
- Cut-Out Diameter: 9¾" (248 mm)



### Profile CRS8 One

- Flangeless Appearance
- 8" Polypropylene Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All One Series
- Sensitivity: 89dB 1W/1m
- Power Handling: 100 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 11½" x 4½"
- 303 mm x 114 mm (with Grille)
- Cut-Out Diameter: 9¾" (248 mm)



### Profile CRS6 Three

- Flangeless Appearance
- 6½" Aluminum Woofer
- Pivoting 1" Aluminum Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 90dB 1W/1m

- Power Handling: 125 Watts
- Adjustable Impedance: 8/6/4 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9⅝" x 4¼"
- 249 mm x 103 mm (with Grille)
- Cut-Out Diameter: 8¾" (210 mm)



### Profile CRS6 Two

- Flangeless Appearance
- 6½" Glass Composite Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Bass and Treble EQ Switches
- Sensitivity: 92dB 1W/1m

- Power Handling: 120 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9⅝" x 4¼"
- 249 mm x 103 mm (with Grille)
- Cut-Out Diameter: 8¾" (210 mm)



### Profile CRS6 One

- Flangeless Appearance
- 6½" Polypropylene Woofer
- Pivoting 1" Silk Tweeter
- WavePlane Technology
- Timbre-Matched to All One Series
- Sensitivity: 92dB 1W/1m

- Power Handling: 100 Watts
- Impedance: 8 Ohm
- Frequency Response: 40Hz - 20kHz
- Diameter x Depth: 9⅝" x 4¼"
- 249 mm x 103 mm (with Grille)
- Cut-Out Diameter: 8¾" (210 mm)



### Profile CRS5.2R

- Flangeless Appearance
- 5¼" Polypropylene Woofer
- ½" Liquid Cooled Polyamide Tweeter
- Sensitivity: 91dB 1W/1m
- Power Handling: 50 Watts

- Impedance: 8 Ohm
- Frequency Response: 55Hz - 20kHz
- Diameter x Depth: 8" x 3¼"
- 203 mm x 83 mm (with Grille)
- Cut-Out Diameter: 6¾" (171 mm)



**Profile CRS3**

- Flangeless Appearance
- 3" Aluminum Woofer
- Timbre-Matched to All Three Series
- Sensitivity: 86dB 1W/1m
- Power Handling: 40 Watts
- Impedance: 8 Ohm
- Frequency Response: 80Hz - 16kHz
- Diameter x Depth: 5 $\frac{1}{8}$ " x 3 $\frac{1}{4}$ "
- 137 mm x 83 mm (with Grille)
- Cut-Out Diameter: 4 $\frac{1}{2}$ " (113 mm)



**Profile AIM7 DT Three**

- Flangeless Appearance
- Pivoting 7" Aluminum Dual Voice Coil Woofer and Rubber Surround
- Dual Pivoting 1" Aluminum Tweeters
- WavePlane Technology
- Bass and Treble EQ Switches
- Timbre Matched to All Three Series
- Sensitivity: 92dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 50Hz - 20kHz
- Diameter x Depth: 9 $\frac{5}{8}$ " x 4 $\frac{1}{4}$ "
- 244 mm x 121 mm (with Grille)
- Cut-Out Diameter: 8 $\frac{1}{2}$ " (210 mm)



**Profile AccuFit CRS7 Three**

- Flangeless Appearance
- 7" Aluminum Woofer
- 3/4" Pivoting Aluminum Tweeter
- Treble Equalization Switch
- Sealed Steel Enclosure
- WavePlane Technology
- Sensitivity: 92dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8 Ohm
- Frequency Response: 50Hz - 20kHz
- STL (Sound Transmission Loss) Feature
- Diameter x Depth: 9 $\frac{5}{8}$ " x 2 $\frac{1}{8}$ "
- 244 mm x 70 mm (with Grille)
- Cut-Out Diameter: 8 $\frac{1}{2}$ " (210 mm)



### Profile AIM Cinema Five

- Flangeless Appearance
- Pivoting 1" Aluminum/Magnesium Tweeter
- Two 5¼" Kevlar® Woofers with Phase Plugs
- Two 6" Kevlar® Impregnated Paper Woofers
- Treble, Mid & Bass EQ Switches
- Bi-Amping Feature
- Timbre-Matched to All Five Series
- Sensitivity: 91dB 1W/1m

- Power Handling: 200 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 35Hz - 20kHz
- Dimensions: (H x W x D) 30¼" x 9" x 4"  
768 mm x 229 mm x 102 mm  
(with Grille)
- Wall Cut-Out: (H x W) 28¾" x 7½"  
730 mm x 191 mm



Indent Only

### Profile AIM Cinema Three

- Flangeless Appearance
- Pivoting 1" Aluminum Tweeter
- Two 5¼" Aluminum Woofers with Phase Plugs
- Two 6" Kevlar® Impregnated Paper Woofers
- Treble, Mid & Bass EQ Switches
- Bi-Amping Feature
- Timbre-Matched to All Three Series
- Sensitivity: 90dB 1W/1m

- Power Handling: 175 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 39Hz - 20kHz
- Dimensions: (H x W x D) 30¼" x 9" x 4"  
768 mm x 229 mm x 102 mm  
(with Grille)
- Wall Cut-Out: (H x W) 28¾" x 7½"  
730 mm x 191 mm



Indent Only

### Profile AIM Cinema One

- Flangeless Appearance
- Pivoting 1" Silk Tweeter
- Two 5¼" Graphite Woofers with Phase Plugs
- Two 6" Kevlar® Impregnated Paper Woofers
- Bass EQ Switch
- Bi-Amping Feature
- Timbre-Matched to All One Series
- Sensitivity: 89dB 1W/1m

- Power Handling: 125 Watts
- Impedance: 8 Ohm Compatible
- Frequency Response: 40Hz - 20kHz
- Dimensions: (H x W x D) 30¼" x 9" x 4"  
768 mm x 229 mm x 102 mm  
(with Grille)
- Wall Cut-Out: (H x W) 28¾" x 7½"  
730 mm x 191 mm



Indent Only

## Profile AIM LCR5 Three

- Flangeless Appearance
- Pivoting Baffle
- Two 5¼" Aluminum/Magnesium Woofers with Phase Plugs
- Pivoting 1" Aluminum/Magnesium Tweeter
- Bass & Treble EQ Switches
- Timbre-Matched to All Three/Four Series
- Sensitivity: 90dB 1W/1m
- Power Handling: 100 Watts
- Adjustable Impedance: 8/6 Ohm
- Frequency Response: 50Hz - 20kHz
- Dimensions: (H x W x D) 17½" x 9" x 4"  
235 mm x 443 mm x 102 mm  
(with Grille)
- Wall Cut-Out: (H x W) 7½" x 14¼"  
190 mm x 362 mm



## Profile AIM LCR5 One

- Flangeless Appearance
- Pivoting Baffle
- Two 5¼" Graphite Woofers with Phase Plugs
- Pivoting 1" Silk Dome Tweeter
- Timbre-Matched to All One Series
- Sensitivity: 89dB 1W/1m
- Power Handling: 80 Watts
- Impedance: 8 Ohm
- Frequency Response: 55Hz - 20kHz
- Dimensions: (H x W x D) 17½" x 9" x 4"  
235 mm x 443 mm x 102 mm  
(with Grille)
- Wall Cut-Out: (H x W) 7½" x 14¼"  
190 mm x 362 mm



## Profile AIM LCR3 Three

- Flangeless Appearance
- Pivoting Baffle
- Two 3" Aluminum Woofers with Phase Plugs
- Pivoting ¾" Aluminum Tweeter
- 2-Position Treble EQ Switch
- Sensitivity: 86dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 78Hz - 20kHz
- Dimensions: (H x W x D) 10½" x 6" x 3"  
254 mm x 146 mm x 76 mm  
(with Grille)
- Wall Cut-Out: (H x W) 9" x 4¾"  
227 mm x 120 mm



## Profile AIM LCR3 One

- Flangeless Appearance
- Pivoting Baffle
- Two 3" Graphite Woofers with Phase Plugs
- Pivoting ¾" Silk Tweeter
- Timbre-Matched to All One Series
- Sensitivity: 85dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohm
- Frequency Response: 80Hz - 20kHz
- Dimensions: (H x W x D) 10½" x 6" x 3"  
254 mm x 146 mm x 76 mm  
(with Grille)
- Wall Cut-Out: (H x W) 9" x 4¾"  
227 mm x 120 mm



## Profile AIM7 MT Three

- Flangeless Appearance
- 7" Aluminum Woofer with Phase Plug
- Pivoting 1" Aluminum Tweeter
- Bass & Treble EQ Switches
- Timbre-Matched to All Three Series
- Sensitivity: 91dB 1W/1m
- Power Handling: 125 Watts
- Impedance: 8/6 Ohm
- Frequency Response: 40Hz - 20kHz
- Dimensions: (H x W x D) 14" x 9½" x 4"  
(at Full Pivot) 356 mm x 241 mm x 102 mm  
(with Grille)
- Wall Cut-Out Dimensions: (H x W) 12¾" x 8⅞"  
324 mm x 206 mm



\* These speakers are L & R specific and only sold in pairs



