



# DESIGNER MARBLE

BESPOKE MOSAICS

## CARE ADVICE

### INSTALLATION

MARBLE MOSAIC MUST BE CUT WITH A WET TILE SAW AND A NEW DIAMOND BLADE AND ADHERED TO A CLEAN DRY SURFACE USING A THIN-SET MARBLE TILE ADHESIVE.

UNSANDED GROUT SHOULD BE MIXED ACCORDING TO MANUFACTURER'S SPECIFICATIONS AND APPLIED TO THE MOSAIC SURFACE FOLLOWING PRE-SEALING. EXCESS GROUT MUST BE REMOVED IMMEDIATELY USING A DAMP CLOTH.

### PRE-SEALING

OUR MARBLE MOSAIC IS PRE-SEALED HOWEVER WE RECOMMEND SEALING THE SURFACE ONCE THE TILE GLUE IS DRY AND PRIOR TO APPLYING GROUT TO THE MOSAIC SURFACE. APPLY AN IMPREGNATOR STONE SEALER LIBERALLY USING A DRY CLOTH OR LAMBSWOOL APPLICATOR, ALLOW TO PENETRATE FOR A MINIMUM OF SIXTY MINUTES AND REMOVE THE EXCESS PRODUCT WITH A CLEAN CLOTH. THIS PROCESS CAN BE REPEATED ONCE THE GROUT HAS BEEN APPLIED AND THE MARBLE HAS BEEN CLEANED.

### CLEANING

MARBLE MOSAIC CAN BE CLEANED WITH WARM WATER AND A MILD DISHWASHING DETERGENT OR STONE SAFE SURFACE SPRAY. WIPE THE SURFACE IMMEDIATELY FOLLOWING CONTACT WITH CITRUS FRUITS, FRUIT JUICE, VINEGAR OR RED WINE AND AVOID BLEACH, ACIDIC CLEANERS OR ABRASIVE HOUSEHOLD CLEANERS.

### MAINTENANCE

SEALING THE MOSAIC SURFACE ANNUALLY WILL ENSURE THE APPEARANCE AND LUSTRE OF THE MARBLE IS PRESERVED FOR A LIFETIME. APPLY AN IMPREGNATOR STONE SEALER LIBERALLY USING A DRY CLOTH OR LAMBSWOOL APPLICATOR, ALLOW TO PENETRATE FOR A MINIMUM OF SIXTY MINUTES AND REMOVE THE EXCESS PRODUCT WITH A CLEAN CLOTH.

---

TELEPHONE 1300 075 933  
EMAIL [INFO@DESIGNERMARBLE.COM.AU](mailto:INFO@DESIGNERMARBLE.COM.AU)  
27 MARENO ROAD TULLAMARINE  
VICTORIA 3043 AUSTRALIA  
[DESIGNERMARBLE.COM.AU](http://DESIGNERMARBLE.COM.AU)  
ABN 19 165 943 331

