

SPECIFICATION SHEET

LED AC DRIVERLESS FLOODLIGHTS



The LED AC Driverless Floodlights are available in 10W-300W and have a black finish.

Applications:

- Commercial Sites • Factories • Leisure Centres



Image shown FLAC100B




Specification

LED:	10-300pcs of SMD 2835
Material:	Aluminium
Colour Temperature:	6000K
Guarantee:	2 Years
Life Expectancy:	>30,000 Hours
Working Temperature:	-20°C - 45°C
Power Factor:	>0.9
Beam Angle:	>120°
CRI:	>80 Ra

Additional Information

- 80lm/W
- Aluminium tray
- Black finish
- Driverless technology
- 3G 0.75mm² 1m Cable included
- Mounting bracket included
- Internal white reflector
- HO5RN-F

Dimensions



Code	Wattage	Lumen Output	Dimensions (L x W x D mm)
FLAC10B	10W	800lm	103 x 83 x 24
FLAC20B	20W	1600lm	160 x 122 x 25
FLAC30B	30W	2400lm	160 x 122 x 25
FLAC50B	50W	4000lm	206 x 160 x 31
FLAC100B	100W	8000lm	270 x 210 x 31
FLAC150B	150W	12,000lm	379 x 279 x 43
FLAC200B	200W	16,000lm	379 x 279 x 43
FLAC300B	300W	24,000lm	445 x 335 x 45