

ACERNO

PRODUCT SPECIFICATIONS

Application
Upholstery

Contents
Top - 100% CPU Polyurethane (Solvent/DMF Free)
Back - 65% Polyester, 35% Cotton

Width
54"

Repeat
N/A

Thickness
40/44 gauge

Roll Length
App. 40yds

General Characteristics

- Abrasion: Exceeds 200,000 double rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis Resistance: 10+ weeks
- ISO1419:1995, Method C, Tropical Test
- Colorfastness to Light: Passes (AATCC 16)
- Colorfastness to bleach (AATCC-3) : passes 1:10 & 1:5 dilution test
- Breaking Strength (ASTM D5034)
- Tear strength (ASTM D2261)

Flammability

CA Bulletin 117-2013; IMO A652 (16) 8.2

Environmental

Solvent/DMF Free, Phthalates Free, FR/Anti-Microbial Additives Free
**Complies with REACH, California Section 01350 VOC Emission Standard*

Cleaning

- W/S, Bleach Cleanable (10:1)
- Stain Removal : Spot cleaning with mild soap and water will remove most of the everyday stains.
- All stains and spills should be addressed immediately. The longer it remains, the more difficult it will be to remove.
- Always test on an inconspicuous area first.



Field



ACT® Registered Certification Marks