



390 Powercat Tiller Order form

HULL FEATURES

- | | |
|---------------------------|-----------------------|
| • Hull length L.O.A | 3900mm |
| • Beam | 1850mm |
| • Fuel capacity | Tote tank with engine |
| • Hull thickness | 4mm alloy |
| • Transom height | 20" |
| • Engine size range | 15-25hp |
| • Recommended engine size | 30hp |
| • Maximum engine size | 40hp |
| • Maximum engine weight | 100kg |
| • Hull weight | 200kg (approximately) |

STANDARD FEATURES

- Flush-mount anchor hatch with slam latch
- Self draining anchor well
- Bollard & bow roller
- Step to casting platform
- Built in rear seats
- 3 year structural hull warranty
- Ultralon Octigrip Floor, Boarding Platform, Bow & Gunnel
- Dual dry storage areas fwd (incl hatches)
- 2x drink holders to gunnel
- 4x rod holders (aft and mid)
- 2x grabrails (transom)

OPTIONS

Aft passenger grabrails (each)
Bow grabrail (pair)
Boarding ladder
Side console
Trolling motor mount & battery mount
Fold down cleats (each)

SEATING OPTIONS

Passenger seat
Rear seat - upholstery

PAINT OPTIONS

Paint - full Nyalic
Paint - hull only
Paint - Nyalic interior/paint exterior
Vinyl to hull sides

U-DEK OPTIONS

Upgrade Octi to U-Dek
Custom U-Dek design
U-Dek foam cleaner