

450 Powercat Cuddy Order form

HULL FEATURES

Hull length L.O.A 4500mmBeam 2070mm

Fuel capacity
Tote Tank with Engine

Hull thickness
4mm Alloy

• Transom height 20"

• Engine size range 40-70hp

Recommended engine size 60hpMaximum engine size 70hp

Maximum engine weight 125kg

Hull weight 400kg (approximately)

STANDARD FEATURES

• Flush-mount anchor hatch with slam latch

- Self draining anchor well
- Bollard & bow roller
- Fully integrated boarding platform
- Built in rear seats
- 2x pedestal seats on pyramid bases
- 2x bilge pumps
- Side shelves
- 3 year structural hull warranty
- Hydraulic steering

- Octigrip Floor, Boarding Platform, Bow & Gunnels
- Dual dry storage areas fwd (incl hatches)
- 2x drink holders to gunnels
- 4x rod holders (aft and mid)
- 2x grabrails (transom)
- Fixed windscreen
- Integrated bait station with storage hatch (transom)
- Wiring loom with 4 way switch panel
- Navigation lights

OPTIONS

HULL OPTIONS

Aft passenger grabrail (each)

Boarding ladder

Ski/tow bracket with rocket launchers

Upgrade transom storage to live bait tank

Add live bait tank window

Trolling motor mount & battery mount

Folding canopy with aluminium frame

Integrated fuel tank, 80lt

Tasman 6-6 Drum winch

Fold down cleats (each)

SEATING OPTIONS

Chilly bin seat base

Upgrade to flip back, reversing seat

Upgrade to bolster seat, slide and swivel

Rear seat - upholstery

PAINT OPTIONS

Paint - full Nyalic

Paint - hull only

Paint - Nyalic interior/paint exterior

Vinyl to hull sides

U-DEK OPTIONS

Upgrade Octi to U-Dek

Custom U-Dek design

U-Dek foam cleaner