

510 Powercat Cuddy Order form

HULL FEATURES

- Hull length L.O.A
- Beam
- Fuel capacity
- Hull thickness
- Transom height
- Engine size range
- Recommended engine size
- Maximum engine size
- Maximum engine weight
- Hull weight

STANDARD FEATURES

- Flush-mount anchor hatch with slam latch
- Self draining anchor well
- Bollard & bow roller
- Fully integrated boarding platform
- 2x pedestal seats on pyramid bases
- 2x bilge pumps
- Side shelves
- 3 year structural hull warranty
- Hydraulic Steering
- Navigation lights

- Octigrip Floor, Boarding Platform, Bow & Gunnels
- 2x drink holders to gunnels
- 4x rod holders (aft and mid)
- 2x grabrails (transom)

5100mm

2330mm

4mm Alloy

90-150hp

115hp

150hp

220kg

25"

Tote tank with engine

490kg (approximately)

- Forward cabin hatch
- Integrated bait station with storage hatch (transom)
- Fixed windscreen
- Wiring loom with 4 way switch panel

OPTIONS

HULL OPTIONS

Bowrails (300mm)

Aft passenger grabrail (each)

Boarding ladder

Ski/tow bracket with rocket launchers

Upgrade transom storage to live bait tank

Add live bait tank window

Trolling motor mount & battery mount

Bimini incl 4x rocket launchers & top canvas

Integrated fuel tank, 100lt

Tasman 6-6 Drum winch

Fold down cleats (each)

SEATING OPTIONS

Chilly bin ready seat base (each) Upgrade seat to flip back, reversing seat Upgrade to bolster seat, slide and swivel

PAINT OPTIONS

Paint - Full Nyalic Paint - Hull Only Paint - Nyalic Interior/Paint Exterior Vinyl to hull sides

U-DEK OPTIONS

Upgrade Octi to U-Dek Custom U-Dek design U-Dek foam cleaner