

HEARTLAND USA®

E-Z 200 / E-Z D

Fits H-D® Softail® 2006-2007 FXST with 200 tire from factory / Fits Deuce® 2000-2007 FXSTD
(Instruction)

We recommend that you mock up bike before you paint parts.
We also recommend that you lower the bike to achieve the desired look.



PARTS LIST

E-Z 200 / E-Z D Includes:

Solo Seat
Steel Fender
Billet Aluminum Struts
2pc. Rock Guard
Deuce Spacer (E-Z D Only)
Light Brackets
Hardware



Required tools needed for installation:

5/16 Allen wrench
9/16 Combination wrench
7/16 Combination wrench
1/2 Combination wrench
Blue Loctite



2466 E. Fender Ave. Suite B Fullerton CA. 92831 Ph: 310-822-2697 Fax: 310-634-1271

www.heartlandbiker.com

We recommend reading through the entire install process before beginning.

1



1. Step back, and take one last look at your stock bike.

4



4. Remove the 4 strut cover bolts (2 on each side). Followed by the other 4 bolts holding the strut covers to the internal struts.

2



2. Start out by removing your stock seat.

5



5. Remove the stock fender and covers, exposing the internal struts.

3



3. Disconnect your ECM unit and the T-signal/Tail lamp connector located to the right of the fuse box.

6



6. Remove the 2 bolts at the bottom of the stock rock guard and pull it out from the top.

7



7. Remove the stock rock guard mounting clips from swing arm.

10



10. Slide the right rock guard down into place and tighten all hardware. (make sure to use Blue Locktite on hardware.)

8



8. Install the lower spacer to the swing arm, from where you just removed the stock clips.

11



11. Cover the stock internal struts using a shop towel to prevent scratching your new paint.

9



9. Attach the upper spacer to the new rock guard (slot facing down). Slide the new rock guard into place.

12



12. Coming from the top, slide your fender down into place. Note: Squeezing the fender might help sliding it into place.

13

13. Once you have the fender in place, try to get the holes to line up the best you can and slide the shop towels out.

16

For Deuce® add supplied 1/4" spacer on left when bolting on the left side strut to frame.

16. Tighten the locknuts down until they are snug.

14

14. Now your ready to install your new Heartland struts. Check to make sure your holes are lined up and slide the studs through the holes.

17

17. Use a little Blue Loctite for the strut bolts. Install and tighten firmly.

15

15. Using the hardware provided, put the washer on first, then the locknut. (No Loctite should be used to secure locknut).

18

NEW! Steel ECM Tray. No more plastic tray.

18. Install the new tray and connect the ECM. You will have to reuse your stock turn signal wiring harness.

19



19. Slip the new seat into place, front tab in first. Set the seat down. Apply pressure to the rear of the seat, sealing the suction cups down.

20



20. Step back and check out your new H-D custom that you just built.

From all of us at Heartland USA. We would like to take this moment to thank you for choosing us and hope you enjoy this kit as much as we do. We strive for perfection and we are always thinking of new and improved ideas to make you bike like no other.

For your convenience, we offer two types of removable second seats with optional attachable travel bags.

We would like to hear your feedback on our products. You can E-mail us at info@heartlandbiker.com or feel free to give us a call (310) 822-2697.

If you have any technical questions or concerns for whatever reason, please do not hesitate to call us. We will be glad to help out anyway we can.

Thanks again and hope to see you out there.

**H L U
S A
HEARTLAND**