



ERGONOMIC | COST-EFFECTIVE | LIGHTWEIGHT | SUPERIOR PERFORMANCE

TITAN-S 200 Air Cooled MIG Gun

200A	60% @ CO ₂ - Gas	0.023" - 0.035" Wire	10ft	15ft	Other Lengths
	40% @ Mixed Gas				
	Tweco® #4 / Lincoln® Connector		0501.0140	0501.0006	Contact Sumig
	Miller® Standard Connector		0501.0005	0501.0007	
	Hobart® Connector		0501.0002	0501.0003	
	Euro Connector		0501.0000	0501.0001	

TITAN-S 200 Flexible Gooseneck Air Cooled MIG Gun

200A	60% @ CO ₂ - Gas	0.023" - 0.035" Wire	10ft	15ft	Other Lengths
	40% @ Mixed Gas				
	Tweco® #4 / Lincoln® Connector		0501.0104	0501.0097	Contact Sumig
	Miller® Standard Connector		0501.0105	0501.0098	
	Hobart® Connector		0501.0004	0501.0099	
	Euro Connector		0501.0106	0501.0108	

SUMIG Recommends 10ft cable lengths for 0.023" Wire

STANDARD CONSUMABLES



Photo	Part #	Description
	0502.1676	Contact Tip 0.023" / 0.6 mm
	0502.1669	Contact Tip 0.030" / 0.8 mm
	0502.1668	Contact Tip 0.035" / 0.9 mm
	0502.1667	Contact Tip 0.040" / 1.0 mm
	0502.1666	Threaded Gas Diffuser TS 200/180/260 46mm
	0502.2000	Short Threaded Gas Dif. TS 200/180/260 32mm
	0500.1039	Gas Diffuser Insulator
	0500.2669	Threaded Nozzle Ø 13x60 mm
	0502.2001	Short Threaded Nozzle Ø 13x47 mm
	0500.1025	Steel Liner 0.023"- 0.035" x 15 ft 0.6-0.9 mm x 4.5 m)

KIT STANDARD CONSUMABLES

(Includes 10 Contact Tips, 1 Nozzle, 1 Gas Diffuser and 1 Insulator)

Photo	Part #	Description
x 10	0502.2060	0.023" / 0.6 mm Kit
	0502.2061	0.030" / 0.8 mm Kit
	0502.2062	0.035" / 0.9 mm Kit

FLEX GUN EASY-TO-REPLACE GOOSENECKS

Photo	Part #	Description
	0502.1993	Flexible Threaded GooseNeck
	0500.1502	45 Degrees Threaded GooseNeck

Distributed by: