

550A

60% @ CO₂ - Gas
40% @ Mixed Gas

0.035" - 3/32"
Wire

10ft

15ft

Other Lengths or Power Pins

Tweco® #4 / Lincoln® Connector

0501.0171

0501.0180

Miller® Connector

0501.0174

0501.0177

Euro Connector

0501.0060

0501.0061

No Power Pin

0501.0062

0501.0063

Contact Sumig

**STANDARD
CONSUMABLES**



Water Cooled Torch Body and Cable








Photo	Code	Description
	0500.2570	Nozzle \varnothing 5/8"x3" / 15.8x75mm <i>* Special Nozzle Dimensions Available. Please consult.</i>
	0502.1150	Gas Diffuser S+ HD
	0500.1148	Gas Diffuser Insulator
	4002.1013	Nozzle O-Ring
	0900.1744	0.035" / 0.90mm
	0900.1316	S+ HD Contact Tip 0.045" / 1.20mm
	0900.1372	1/16" / 1.60mm
	0900.1493	S+ CuCrZr Contact Tip 3/32" / 2.40mm

Photo	Description	10ft	15ft
	Steel Liner 0.035"- 0.045"	0500.1167	0500.1168
	Steel Liner 0.045"- 1/16"	0500.1169	0500.1170
	Steel Liner 1/16"- 3/32"	0502.1141	0502.1642

**WORKS
PERFECTLY WITH**

**Sold Separately*

Photo	Part#	Description
	WCL0001	<p>WC12 Water Cooler</p> <ul style="list-style-type: none"> o Operates in both vertical and horizontal position. o Factory set at 50 psi adjustable to 100 psi o 2 gallon reservoir o 115 or 230 vac / 1 ph-50 / 60 Hz o 12,000 BTU o Dimensions: 9"L x 9"W x 26"H o 1/4" FPT (water in / out) with 5/8" LH Standard Inert Gas Fitting o Rugged polyethylene non-dent construction o Visible water level through tank o Thermal overload o Net weight: 33 lbs / 15 kg



SUMIG USA CORPORATION
8600 Commodity Circle #159
Orlando, FL 32819

☎ 1 800 503-9717
🌐 www.sumigusa.com
✉ sumigusa@sumig.com